

PROCEDURE 7 - Hazard Communication

<u>Table of Contents</u>	<u>Page</u>
Synopsis	7-ii
Hazard Communication Checklist	7-iv
7 HAZARD COMMUNICATION	7-6
7.1 Purpose and Scope	7-6
7.2 Definitions	7-6
7.3 Procedure	7-6
7.4 Quality Control	7-6
7.5 Responsibilities	7-7
7.6 References	7-8
7.7 Addenda	7-8
ADDENDUM I	7-Addendum I-1
HAZARD COMMUNICATION PROGRAM KIT	7-1
SECTION A	7-A-1
Executive Summary	7-A-1
SECTION B	7-B-1
Compliance Guidance	7-B-1
SECTION C	7-C-5
National Weather Service Hazard Communication Program	7-C-5
SECTION D	7-D-1
Worksite Hazardous Chemical List	7-D-1
Worksite Material Safety Data Sheets	7-D-1
SECTION F	7-F-1
Labeling Information	7-F-1
SECTION G	7-G-1
Work Site Training Records	7-G-1
SECTION H	7-H-1
NWS Hazardous Chemical List Requirements	7-H-1
SECTION I	7-I-1
Material Safety Data Sheets Requirements	7-I-1
SECTION J	7-J-1
NWS Material Safety Data Sheet Request	7-J-1
SECTION K	7-K-1
Training Program	7-K-1
SECTION L	7-L-1
Cleanup and Disposal of Typical Hazardous Materials and Wastes	7-L-1
ADDENDUM II	7-Addendum II-1
Hazard Communication WFO Springfield, MO	7-Addendum II-1

Synopsis

The purpose of this procedure is to educate all personnel about chemical hazards in the workplace. This procedure applies to all NWS facilities, work locations, and employees.

Initial Implementation Requirements:

- **Analyze Site Operations versus Procedure Requirements**
 - Identify Hazardous Chemicals on site. (*B.3.2, C.1*)
 - Inspect all labels on each container containing a hazardous chemical. (*B 3.4, C.4*)
- **Develop/Obtain Documentation/Information Required for Site**
 - Prepare a list of hazardous chemicals (*C.1*)
 - Develop site-specific Hazard Communication Program. (*7.3.3*)
 - Material Safety Data Sheets (MSDS) (*B.3.3, C.2.1*)
 - Procedures for control of chemical purchases. (*B.3.2, C.3*)
 - Training Lesson Plans. (*C.5, K*)
 - Procedure for updating chemical list. (*B 3.2, C.1*)
 - Procedure for contractor's compliance. (*C.10*)
- **Designate Person to Administer Hazard Communication Program Requirements**
- **Provide Local Training of Site Personnel**
 - MSDS (*C.5, K*)
 - Labeling of Hazardous Chemical Containers. (*K*)
 - Chemical Hazards in the workplace. (*C.5, K*)
 - Emergency Procedures (*C.5, K*)
 - Hazardous Materials Cleanup and Disposal. (*L*)
- **Inventory Material/Equipment (Procure as required)**
 - Container Labels. (*7.5.2b, B.3.4*)
 - Training Videos (*7.5.2b, K*)
 - Spill Cleanup Equipment. (*7.5.2b, L*)

Recurring and Annual Task Requirements:

- **Perform Inspections/Assessment/Testing**
 - Inspect labels on each container containing a hazardous chemical. (*B. 3.4, C.4*)
- **Review/Update Documentation/Information required for Site**
 - Maintain a list of hazardous chemicals (*C.1*)
 - Update site-specific Hazard Communication Program. (*7.3.3*)
 - Material Safety Data Sheets (MSDS) (*B.3.3, C.2.1*)
 - Procedures for control of chemical purchases. (*B.3.2, C.3*)
 - Training Lesson Plans. (*C.5, K*)
 - Procedure for updating chemical list. (*B.3.2, C.1*)
 - Procedure for contractor's compliance. (*C.10*)
- **Provide Refresher Hazard Communication Training of Site Personnel** (*C.5*)
- **Inspect/Replace/Maintain Material/Equipment**
 - Container Labels. (*7.5.2b, B.3.4*)
 - Training Videos (*7.5.2b, K*)
 - Spill Cleanup Equipment. (*7.5.2b, L*)

This Page is Left Intentionally Blank

Hazard Communication Checklist

Requirements	Reference	YES	NO	N/A	Comments
Is initial and annual review of this procedure conducted and documented?	7.4.2				
Has a written Hazard Communication Program been developed?	7.3.3, C				
Has the Hazard Communication training been provided to all personnel?	K				
Have all affected employees read, understood and complied with the requirements of this procedure?	7.5.4a				
Has the list of hazardous chemicals been prepared and updated semi-annually?	B.3.2 C.1				
Are employees trained on hazards associated with chemicals present in the workplace and how they can protect themselves from these hazards?	K C.5				
Are all containers containing Hazardous Chemicals labeled, tagged, and include the identity and appropriate warnings of the hazardous chemical?	B.3.4 C.4				
Have facility personnel been trained on the use, interpretation and importance of labeling?	B.3.4 C.5				
Are employees trained in the use and interpretation of Material Safety Data Sheets (MSDS)?	K C.5				
Are there complete and legible MSDS for all Hazardous chemicals at this facility?	B.3.3 C.2				
Are MSDS kept in a location(s) so that they are readily available to all personnel on all shifts?	B.3.3 C.2				
Are employees trained on who to contact and what to do	B				

Requirements	Reference	YES	NO	N/A	Comments
in an emergency?	C.5				

7 HAZARD COMMUNICATION

7.1 Purpose and Scope

As part of its goal to provide a safe and healthful workplace, the National Weather Service (NWS) is promulgating this procedure to educate all personnel about chemical hazards in the workplace. This procedure applies to all NWS facilities, work locations, and employees.

7.2 Definitions

Field Office. A Field Office may include the following: Weather Forecast Office (WFO), River Forecast Center (RFC), Weather Service Office (WSO), and a Data Collection Office (DCO).

MSDS - Material Safety Data Sheet.

Operating Unit. For the purpose of this procedure, Operating Unit includes the National Centers for Environmental Prediction (NCEP), National Data Buoy Center (NDBC), NWS Training Center (NWSTC), National Reconditioning Center (NRC), Radar Operations Center (ROC), or the Sterling Field Support Center (SR&DC).

OSHA. Occupational Safety and Health Administration.

Station Manager. For the purpose of this procedure, the Station Manager shall be either the NWS Regional Director; Directors of Centers under NCEP (Aviation Weather Center, NP6; Storm Prediction Center, NP7; and Tropical Prediction Center, NP8); Directors of the NDBC, NWSTC, and Chiefs of NRC, ROC and SFSC facilities; or Meteorologist in Charge (MIC), Hydrologist in Charge (HIC), or Official in Charge (OIC).

7.3 Procedure

7.3.1 The Station Manager shall ensure that the facility implements a comprehensive Hazard Communication Program which complies with the requirements of OSHA 29 CFR 1910.1200, "Hazard Communication."

7.3.2 Each facility shall develop a site-specific Hazard Communication Program using the template provided in Addendum I, Section C: "NWS Hazard Communication Program."

7.3.3 The Safety or Environmental/Safety Focal Point shall oversee the implementation and maintenance of the facility's Hazard Communication Program.

7.4 Quality Control

7.4.1 Regional or Operating Unit Environmental/Safety Coordinators

- a. Shall perform an annual assessment of the regional headquarters facilities or operating unit to monitor and promote compliance with the requirements of this procedure.
- b. Shall perform assessments or designate personnel to perform assessments of all field offices to monitor and promote compliance with the requirements of this procedure every two years.

7.4.2 Station Manager

Shall review or delegate review, of this procedure on an annual basis to ensure that the facility is complying with its requirements. Confirmation of this review shall be forwarded to the Regional or Operating Unit Environmental/Safety Coordinator.

7.4.3 NWS Headquarters (NWSH)

- a. The NWS Safety Office shall perform an annual assessment of the NWSH facilities to ensure that the facilities are in compliance with this procedure.
- b. The NWSH Safety Office shall periodically perform an assessment of the regional headquarters and field offices to ensure compliance with this procedure. The frequency of these regional and field office assessments shall be determined by the NWSH Safety Office.
- c. Requests for clarification concerning this procedure shall be directed to the NWSH Safety Office.

7.5 Responsibilities

7.5.1 Regional or Operating Unit Environmental/Safety Coordinators*

Shall monitor and coordinate to promote compliance with the requirements of this procedure for the regional headquarters, and field offices or operating units.

7.5.2 Station Manager*

- a. Shall have oversight over the implementation of this procedure, and ensure that the requirements of this procedure are followed by individuals at the NWS facility.
- b. Shall ensure that initial and periodic inventory of container labels, training videos, spill clean up and other safety equipment is accomplished and adequate stock is maintained.

7.5.3 Safety or Environmental/Safety Focal Point*

- a. Shall ensure that any responsibilities delegated to them by the Station Manager are implemented in accordance with the requirements of this procedure.
- b. Shall oversee the implementation and maintenance of the facility's Hazard Communication Program.

7.5.4 Employees

- a. Employees affected by this procedure are required to read, understand and comply with the requirements of this procedure.
- b. Report unsafe or unhealthful conditions and practices to their supervisor or safety focal point.

NOTE: * - Reference NWS PD 50-11 for complete list of responsibilities
<http://www.nws.noaa.gov/directives/050/pd05011a.pdf>

7.6 References

Incorporated References. The following list of references is incorporated as a whole or in part into this procedure. These references can provide additional explanation or guidance for the implementation of this procedure.

U.S. Department of Labor, Occupational Safety and Health Administration, 29 CFR 1910.1200, "Hazard Communication."

7.7 Addenda

Addendum I: Hazard Communication Program Compliance Kit

Addendum II: Hazard Communication, WFO Springfield MO

ADDENDUM I

HAZARD COMMUNICATION PROGRAM KIT

SECTION A

Executive Summary

A standardized NWS Hazard Communication Program template is found in Section C. It meets the *minimum* OSHA requirements. A complete Hazard Communication Program can be viewed on the NWS Environmental and Safety Compliance Home Page, <http://www.oso3.nws.noaa.gov/safety/hazcom.htm>. The document can be downloaded in WP format.

The Station Manager or his/her designee (e.g., Safety or Environmental/Safety Focal Point) shall review the Hazard Communication Program template presented in Section C and fill in the blanks to include unique information about each work site. The written program shall be available for employees to review. The program consists of the following sections:

Section	Description
A	Executive Summary
B	Compliance Guidance
C	NWS Hazard Communication Program (template)
D	Worksite Hazardous Chemical List
E	Worksite Material Safety Data Sheets (MSDS)
F	Label Information (informative)
G	Worksite Training Records
H	NWS Hazardous chemical List Requirements and Sample Hazardous Chemical list form
I	Material Safety Data Sheet (MSDS) Requirements.
J	NWS Material Safety Data Sheet Requests. (1) Sample letter for requesting a MSDS. (2) Sample letter for requesting additional information about a MSDS, and (3) MSDS Request File sheet
K	Training Program.
L	Cleanup and Disposal of Typical Hazardous Materials and Wastes.

SECTION B

Compliance Guidance

B.1 Introduction. About thirty two-million workers in the United States are potentially exposed to one or more chemical hazards. There are an estimated 575,000 existing chemical products, and hundreds of new ones are being introduced annually. This poses a serious problem for exposed workers and their employers. Chemical exposure may cause or contribute to many serious health effects such as heart ailments, kidney and lung damage, sterility, cancer, burns, and rashes. Some chemicals may also be safety hazards and have the potential to cause fires and explosions and other serious accidents.

Because of the seriousness of these safety and health problems, and because many employers and employees know little or nothing about them, in 1983 the Occupational Safety and Health Administration (OSHA) issued a standard called **Hazard Communication** that applies to employers in the manufacturing sector of industry. The scope of the standard was expanded in 1987 to include employers in the non-manufacturing sector and Federal Government. The finalized standard was promulgated on August 24, 1987, and amended in March 1997. Further explanations are found in the Federal Register 52 (163): 31852-31886, August 24, 1987. The Hazard Communication Standard can be viewed:

- at http://www.osha-slc.gov/OshStd_data/1910.1200.html, or
- via link from the NWS Environmental and Safety Compliance Home Page, <http://www.oso3.nws.noaa.gov/safety/hot.htm>

The basic goal of the standard is to ensure that supervisors and employees know about chemical hazards and know how to protect themselves. This knowledge, in turn, should help to reduce the incidence of chemical source illnesses and injuries.

B.2 What the Standard Requires. The Hazard Communication Standard establishes uniform requirements to assure that the hazards of all chemicals imported, produced or used in U.S. workplaces are evaluated for physical and health hazards, and that the resultant hazard information and associated protective measures are transmitted to supervisors and potentially exposed employees by means of labels on containers and material safety data sheets (MSDS).

This Hazard Communication Program ensures that all National Weather Service (NWS) supervisors receive the information they need to inform and train their employees properly and to assure that employee protection programs are in place. It also provides necessary hazard information to the staff, so they can participate in, and support, the protective measures at their workplaces.

B.3 How to Comply with the Standard. The NWS Station Manager shall ensure that the field office complies with the standard and that a site-specific hazard communication program is developed. The Station Manager shall designate personnel who shall be responsible for development and maintenance of the program. See paragraph B.3.5 for more details. The following is a process to be used by the Safety or Environmental/Safety Focal Point in developing a Hazard Communication Program unique to their office.

B.3.1 Read the Standard. See the NWS Environmental and Safety Compliance Home Page (<http://www.oso3.nws.noaa.gov/safety/hot.htm>) to view the Standard (29 CFR 1910.1200). Ensure that the provisions of the Standard are understood.

B.3.2 List the Hazardous Chemicals in the Workplace.

- Walk around the workplace, read the labels of all the containers, and list the identity of materials that may be hazardous; the manufacturer's product name, manufacturer, quantity on hand, location where product is stored, and the work area where the product is used (see table in Section D). Be sure to include hazardous chemicals that are generated in the work operation but are not in a container (e.g., welding fumes, soldering fumes, etc.) and compressed gases.
- Ensure that chemical products purchased through the Consolidated Logistics System (CLS) which are classified as hazardous are listed.
- Review the chemical hazards list and determine whether any substances are exempt [see paragraph (b) of the referenced standard for exemptions], e.g., pesticides, food additives, cosmetics.
- Establish a file on hazardous chemical products used in the workplace, and include copies of the latest MSDSs, and any other pertinent information.
- Develop procedures to keep the list current. The Safety or Environmental/Safety Focal Point shall be responsible for maintaining the procedures. When new products are used or purchased, add them to the list. Establish purchasing procedures. See Section C, paragraph C.3, for details.

B.3.3 Obtain Material Safety Data Sheets for All Chemical Substances.

- If there is no MSDS for a hazardous substance in the workplace, request a copy from the chemical manufacturer, distributor or importer as soon as possible (See Section J for a sample letter requesting an MSDS). In addition, the Internet can be used to obtain missing MSDS (e.g., <http://hazard.com>). An MSDS shall accompany or precede the shipment from a distributor or the National Logistics Support Center (NLSC) and shall be used to obtain identifying information such as the chemical name and the hazards of a particular substance.
- Review each MSDS to be sure that it is complete, legible, and clearly written. The MSDS shall contain the physical and chemical properties of a substance, as well as the physical and health hazards, routes of exposure, precautions for safe handling and use, emergency and first-aid procedures, and control measures. See Section I for MSDS requirements, a sample MSDS, and other information.

- If the MSDS is incomplete or unclear, contact the manufacturer or importer to get clarification on the missing information.
- If the MSDS contains trade secret information, make sure that an emergency number is included.
- Make sure the MSDS is available to facility staff, volunteer observers, contractors, and regional environmental/safety coordinators.
- Upon request, allow a representative of the Assistant Secretary for Occupational Safety and Health (OSHA inspector) to see MSDS files.

B.3.4 Make Sure That All Containers Are Labeled. The manufacturers, importers or distributors are responsible for labeling containers, but both the supervisors and facility staff shall adhere to the following:

- Ensure that all containers of hazardous substances in the workplace are labeled, tagged or marked and include the identity of the hazardous chemical, and the appropriate hazard warnings. Container labels for purchased chemicals shall also include the name and address of the chemical manufacturer, importer, or other responsible party.
- Check all incoming shipments of hazardous chemicals to be sure that they are labeled.
- If a container is not labeled, obtain a label or the label information from the **manufacturer, importer, or other responsible party** or prepare a label using information obtained from these sources. Do not try to “guess” if you are not sure what is in the container.
- Do not remove or deface existing labels on containers unless the container is immediately marked with the required information.
- Remove all old labels before using a container for other products.
- Instruct facility staff on the importance of labeling portable receptacles into which they have poured hazardous substances. If the portable container is for their immediate use, the container does not have to be labeled; however, such a container shall be emptied after the employees leave the area.

B.3.5 Develop and Implement a Written Hazard Communication Program. This program shall include:

- material safety data sheets;
- container labeling and other forms of warnings;
- employee training based upon the hazardous chemicals list, MSDSs, and labeling information; and

- methods for communicating hazards and protective measures to facility staff and others.

Subsequent sections of this kit will discuss each of these steps in more detail and provide samples of the material discussed and lists of products, services, and other resources. See Section C, for the general template of the standardized NWS Hazard Communication Program. Review it, fill in the blanks and add any information specific to the site. In order to implement the Program, the Station Manager and other site supervisors shall be actively involved in the process.

If you need further assistance with program development and training, contact the DOC Regional Safety and Health Manager at the pertinent Administrative Support Center (ASC), the NWS Regional Environmental/Safety Coordinator, or the NWS Safety Officer.

B.4 Checklist. The following checklist can assist Station Manager in their evaluation of the Hazard Communication Program.

- Yes ___ No ___ Reviewed hazardous chemicals at the worksite.
- Yes ___ No ___ Established a master hazardous chemical list.
- Yes ___ No ___ Obtained MSDS for each hazardous chemical in use.
- Yes ___ No ___ Developed and implemented procedures to ensure that all incoming hazardous chemicals are labeled.
- Yes ___ No ___ Reviewed each MSDS for completeness (Is all required information there?)
- Yes ___ No ___ Ensured MSDS are readily available, where necessary.
- Yes ___ No ___ Prepared a written Hazard Communication Program.
- Yes ___ No ___ Developed and implemented processes to communicate hazards to facility personnel.
- Yes ___ No ___ Informed facility staff of protective measures for hazardous chemicals used in the workplace.
- Yes ___ No ___ Alerted facility staff to other forms of warning that may be used.

<p>NOTE: In order to aid in the management of this procedure, only the minimum and essential hazardous materials and products should be purchased and stored.</p>
--

SECTION C

National Weather Service Hazard Communication Program

The following written Hazard Communication Program has been established for:

National Weather Service Office: _____
Region: _____
Address: _____

It is prepared to comply with the U.S. Department of Labor, Occupational Safety and Health and Administration Standard Title 29 Code of Federal Regulations (CFR) Part 1910 Section 1200, Hazard Communication standard requirements.

The Station Manager at this site:

(Meteorologist In Charge, Hydrologist in Charge, or Official In Charge)

is responsible for the occupational safety and health of the personnel and the Hazard Communication program at the site. Functional responsibility for the Hazard Communication Program has been delegated to:

_____ (Safety or Environmental/Safety Focal Point)
name

The Safety or Environmental/Safety Focal Point shall review and update the program on a semiannual basis. This program applies to all worksites associated with (circle one):

- a. Weather Forecast Office (WFO)
- b. Weather Forecast Office/River Forecast Center (WFO/RFC)
- c. Weather Service Office
- d. Data Collection Center
- e. Operating Unit (e.g., NCEP, NDBC, etc.)
- f. Other

NWS employees, their designated representatives, and contractors at this facility and upon request, the Occupational Safety and Health Administration (OSHA) representatives, and emergency and medical service providers have access to this written Hazard Communication Program at the following location: _____

The worksites listed on this page are sites where NWS personnel may be exposed to the chemical hazards under normal working conditions or during an emergency situation.

Locations Associated with the WFO or WFO/RFC			
Site Location:		State:	
List of the offices, WSR-88D Radar Data Acquisition (RDAs) sites, Upper Air Inflation Buildings (UAI Bs), Automated Surface Observing System (ASOS) sites, National Oceanic and Atmospheric Administration (NOAA) Weather Radio, cooperative stations, transition power maintenance shelters, storage sites, etc., associated with this Weather Forecast Office (WFO) or WFO/River Forecast Center (RFC) or Operating Unit.			
Type of Facility/Description		Location	

C.1. Hazardous Chemical List. The Station Manager has the primary responsibility to ensure that a list of hazardous chemicals used at the field office or Operating Unit and associated sites is prepared and kept current. The Safety or Environmental/Safety Focal Point or Station Manager’s designee _____ shall develop and update the master hazardous chemical list semiannually. A new item shall be added on the master chemical list after the Safety or Environmental/Safety Focal Point has reviewed the material safety data sheet (MSDS) and cleared it for purchase (see paragraph C.3 for purchasing requirements). Only the Safety or Environmental/Safety Focal Point or the station manager’s designated representative can update the master hazardous chemical list. Personnel in charge of associated sites are responsible for updating the site hazardous chemical list in accordance with the master list.

Section D contains a master list of all known chemical products and items containing chemicals to which employees at this site are or may be potentially exposed (e.g., via spills). Separate lists are available for RDAs, UAI Bs, ASOS, NOAA Weather Radio, cooperative stations, etc. and are posted and accessible to fire department or other emergency response organization(s) personnel during emergency situations. (Local municipal fire officials may request specific arrangements for displaying the lists outside the building(s)).

The Worksite Hazardous Chemical List includes the following:

- a. product/generic name, as shown on the label and MSDS (names shall be identical);

- b. manufacturer's or distributor's address, and, if available, telephone number;
- c. generic name;
- d. operational area used;
- e. quantity on hand;
- f. date entered into the system;
- g. National Stock Number (NSN)/Agency Stock Number (ASN), if applicable; and
- h. location where used or stored.

It is recommended to have list organized alphabetically, by product name and/or by manufacturer.

C.2. Material Safety Data Sheets. MSDS provide specific information on the chemical product. OSHA requirements for MSDS and its format are described in Section E. The MSDS for all chemicals to which employees may be exposed at this site are maintained in (*circle one*):

- a. Section E
- b. Under separate cover.

The Safety or Environmental/Safety Focal Point is responsible for compiling and maintaining a complete master set of MSDSs for chemical products identified on the hazardous chemical listing (see Section D). The MSDS shall be a fully completed OSHA form 174 (See Section I) or an equivalent.

For products already in use at NWS facilities for which there are no current MSDS, the Safety and Environmental/Safety Focal Point shall ensure that a corresponding MSDS is obtained from the manufacturer or vendor.

If a product is ordered through the Consolidated Logistics System (CLS), the shipment shall automatically include MSDS(s). If the MSDS is not included with a shipment, the ordering employee shall contact the National Logistics Support Center (NLSC) and request the corresponding MSDS. All purchase requisitions for new chemical products shall be reviewed and cleared by the Safety or Environmental/Safety Focal Point, as described in paragraph 3. The MSDS shall be submitted to the Safety or Environmental/Safety Focal Point, who shall assure that it contains all information required by the standard. An MSDS checklist is included in Section J.

The Safety or Environmental/Safety Focal Point shall contact a manufacturer or vendor if within a reasonable time, an MSDS has not been received, or additional clarification and research is necessary. It is advisable to contact the manufacturer's MSDS Technical Service Department first by telephone. When this approach is not successful, the Safety or Environmental/Safety Focal Point shall contact the manufacturer by letter (see Section I for sample letters requesting MSDS or additional information). A copy of the letter shall be retained to document efforts to obtain the MSDS.

The Safety or Environmental/Safety Focal Point shall ensure that MSDS containing trade secret chemical components includes the manufacturer's emergency number. The manufacturer shall disclose the identity of a trade secret component in case of medical emergency to a treating

physician. If the product with a trade secret component requires monitoring or other special protective measures, industrial hygiene professionals have a right to require the identity of trade secret components. The Safety or Environmental/Safety Focal Point shall contact the DOC Regional Safety and Health Manager (RSM) at the pertinent Administrative Support Center (ASC), or the NWS Regional Environmental/Safety Coordinator for technical advice in such cases.

C.2.1 MSDS Sets to Maintain. A master MSDS set shall be maintained at the field office or Operating Unit as part of the Hazard Communication Program. Maintenance of MSDS sets at all collocated sites is recommended. Uniquely defined MSDS subsets shall be available at all remote locations and maintained by the Safety or Environmental/Safety Focal Point or other personnel designated by the Station Manager for the following sites:

- RDA,
- UAIB and/or balloon inflation launching shelter (BILS),
- ASOS
- NOAA Weather Radio
- Cooperative Stations (if chemical products are used)
- Transition power maintenance shelter (TPMS),
- Storage sites, and
- Other sites associated with the facility: _____

In addition, supervisors shall ensure that applicable MSDS are available within individual work areas under their control.

Copies of MSDS can be obtained from the Safety or Environmental/Safety Focal Point.

C.3 Purchasing Requirements. Purchase orders for products that are hazardous or may contain hazardous chemicals/materials shall include a provision, or be accompanied by a written request, to the vendor or supplier that:

- a. An up-to-date MSDS is provided,
- b. Containers bear required identification and warning labels (see paragraph C.4 for labeling requirements), and
- c. Department of Transportation (DOT) requirements for shipment are met.

Prior to the acquisition of new chemical products, the MSDS for those products shall be obtained and forwarded to the Safety or Environmental/Safety Focal Point for review in order to determine if the potential for physical and health hazards exists, and if there are any special requirements for shipment, disposal, and storage. If working with the product would present more than a minor health hazard and require special preventive measures (local exhaust, air monitoring), the usage of such a product shall be discouraged. The product shall be replaced by less hazardous alternatives, if available. NWS employees are mandated to actively search for viable replacement for hazardous products so as to replace them with environmentally 'friendly' products that are less hazardous to human health and the environment. Product cost estimates shall include all expenditures for operating and disposing of that product. This includes the costs

for the initial purchase of the product as well as the use of personal protective equipment and the proper disposal of a used product or residue.

While MSDS are not required to be physically attached to a shipment, they shall accompany or precede the shipment. When the manufacturer/supplier fails to send an MSDS with a shipment, the Safety or Environmental/Safety Focal Point or his/her designee shall obtain one from the manufacturer/supplier.

When purchasing hazardous materials from the foreign companies, NWS personnel shall ensure the following:

- a. Import of hazardous material(s) into the U.S. is not prohibited by any U.S. agency and/or regulations.
- b. Shipment of hazardous material(s) into U.S. is performed in accordance with applicable U.S. DOT regulations.

C.4. Container Labeling and the Use of Placards. Chemical manufacturers, importers, and distributors are mandated by law to label, tag, or mark all containers leaving their plants or warehouses. Unlike the MSDS, the label is not an exhaustive description of the chemical substance. Rather, the label is meant to warn users of health and/or chemical hazards. At a minimum, labels shall list:

- a. name of the chemical, and common names, if any;
- b. signal word for hazard; CAUTION, DANGER, WARNING, etc., and hazard statement (see Section F for examples); and
- c. the name and address of the manufacturer, importer, distributor, or responsible party.

In most cases, chemical products purchased in retail stores have the required labeling. Products purchased in bulk from wholesale distributors or supply houses are more likely to have labeling problems and, therefore, shall be thoroughly checked.

Personnel who purchase or receive shipments shall verify that each container's label contains all the information specified in subparagraphs a, b, and c. The following additional requirements shall be met:

- a. the chemical name shall be identical with the one listed on the MSDS. For items ordered through CLS, there shall be a national stock number (NSN) and agency stock number (ASN) on the label;
- b. labels shall be legible and in English;
- c. labels shall not be defaced or otherwise damaged; and
- d. container labeling shall be in conformance with hazardous material transportation regulations promulgated by Department of Transportation (DOT) and set forth in Title 49 CFR. DOT requires proper shipping name, UN ID #, and hazard labels on shipping container.

If any problems are discovered, shipments shall not be accepted, and the Safety or Environmental/Safety Focal Point shall be notified. If the problem can not be resolved locally, the NWS Regional Environmental/Safety Coordinator, the NOAA Regional Environmental

Compliance Officer (RECO), or DOC Regional Safety Manager (RSM) at respective ASC shall be contacted for advice regarding further action.

Station managers and supervisors are responsible for ensuring that personnel use only labeled/marked containers. To comply with this requirement, existing unlabeled containers shall be labeled (if the content is known) and any new purchase or shipment shall be checked before the product is used.

To further ensure that employees are aware of the chemical hazards of materials used in their work areas, supervisors for each work area and/or shift shall ensure that all secondary containers are labeled. Any container label that becomes damaged shall be replaced. This label may be replaced with either an extra copy of the original manufacturer's label, with generic labels [National Fire Protection Agency (NFPA), Department of Defense (DoD)] or any hand printed in indelible ink that correctly states all data required by subparagraphs a, b, and c (see G for label samples). When transferring chemicals from one container to another (e.g., transfer of a solvent from a 5-gallon container into a 1-gallon can), the person responsible for the transfer is also responsible for the proper labeling of the new container.

Labels may not be required on temporary **portable containers** in which chemicals are:

- a. transferred from labeled containers,
- b. when such a container is intended for the transferring employee's immediate use,
- c. the quantity does not exceed a one day supply, and
- d. the container is used only when an employee is present.

If all of these conditions are not satisfied, the container shall be labeled. Care shall be taken by an employee and supervisor to assure that chemicals are not disposed into temporary containers that previously held incompatible chemicals, unless the containers are properly cleaned.

<p>NOTE: No flammable material may be placed into temporary containers not designated for flammables.</p>
--

Placards or signs which convey the hazard information may be posted in lieu of container labels for stationary containers within a work area which have similar content and hazards, e.g., hydrogen for generators and hydrogen storage area.

The Safety or Environmental/Safety Focal Point shall inspect container labeling at least semiannually in conjunction with the hazardous list and MSDS update. Any unlabeled containers of an unknown content and surplus chemical products shall be disposed of by a certified disposal company. There are a number of Federal and state regulations that govern the handling, transport, storage, and disposal of hazardous chemicals. Any surplus activity shall be planned ahead including accumulation, storage, and disposal of surplus chemicals. Surplus activities shall be coordinated with RECO and the NWS Regional Environmental/Safety Coordinator.

Pesticides, foods, food additives, colorings, drugs, and consumer products that are controlled by other federal agencies and laws do not require labeling under the OSHA Hazard Communication Standard.

C.5. Employee Training and Information. NWS personnel who (even occasionally) work with, purchase, or are potentially exposed to chemicals shall receive initial training on the Hazard Communication Program. The Safety or Environmental/Safety Focal Point shall initially receive comprehensive classroom type environmental and safety training that includes training on the requirements of the Hazard Communication Standard.

The Station Manager, along with the Safety or Environmental/Safety Focal Point shall determine which station or operating unit personnel have not yet received Hazard Communication training and need to be trained. A recommended source of training is the audio/video Federal Hazard Communication Program, specifically developed for the Federal Government personnel. More information can be found in Section K, Training Program. The Safety or Environmental/Safety Focal Point shall assume an active role in personnel training. The training program shall include the following topics:

- a. an overview of the requirements contained in OSHA standard 29 CFR 1910.1200;
- b. chemical and physical properties (flashpoint, reactivity, etc.) of hazardous materials and associated physical hazards (explosive, flammable, etc.);
- c. health hazards, including signs and symptoms of exposure and routes of entry;
- d. how to interpret labels and MSDS;
- e. methods and observation techniques used to determine the presence or release of hazardous chemicals in the work area (such as monitoring, visual appearance, or odor, etc.);
- f. how to lessen or prevent exposure to the hazardous chemicals through usage of safe work practices, engineering controls (ventilation), and personal protective equipment;
- g. chemicals present in the work area;
- h. location and availability of the written Hazard Communication Program, hazardous chemical lists, and MSDSs; and
- i. emergency procedures to follow if an employee is exposed to these chemicals.
- j. spill clean up and disposal of typical NWS hazardous materials and wastes.

Each new employee who has not been trained shall receive the initial training. Upon completion of the initial training, each employee shall sign the training form (see Section G) or a form approved by the Station Manager.

When new chemicals or chemical products are introduced into the work area, the Safety and Environmental/Safety Focal Point shall:

- a. review the MSDS associated with the chemical products,
- b. identify potential hazards and determine hazard control requirements, if applicable, and
- c. ensure that all employees working with or exposed to the hazardous chemicals are properly trained in their use.

Additional training of NWS personnel shall be done whenever a new hazard is introduced into a workplace. Refresher training shall take place based upon an evaluation by the Station Manager

along with the Safety or Environmental/Safety Focal Point. The need for refresher training shall be based on the employee's demonstration that he/she has less than a thorough understanding of the Hazard Communication Program or based on personnel turnover.

C.6. Hazardous Non-Routine Tasks. Infrequently, NWS employees are required to perform hazardous non-routine tasks. Prior to starting work on such projects, affected employees shall be given information by their supervisor and the Safety or Environmental/Safety Focal Point about the hazards to which they may be exposed during such activity. If more technical advice is required, the NWS Regional Environmental/Safety Coordinator, RECO, or RSM at ASC should be contacted.

The information shall include:

- MSDS and description of other physical and health hazards,
- personal protective equipment and safety measures the employee shall use,
- measures that the Station Manager or his designee has taken to lessen the hazards associated with non-routine task, including area ventilation, assignment of a second person or safety observer, spill emergency procedures, etc.

C.7. Chemicals in Unlabeled Pipes. Work activities are often performed by employees in areas where chemicals are transferred through unlabeled pipes. Pipes are not required to be labeled; however, employees shall be informed of their content. The field office or Operating Unit may have the following unlabeled pipes: potable water, sewer, oil piping, air conditioning, equipment piping (e.g., air conditioning piping contains Freon that is asphyxiant; maintenance on such piping shall be done only by certified mechanics with specialized recovery equipment).

Prior to starting work in these areas, employees shall contact the responsible supervisor for information regarding:

- the chemical(s) in the pipes,
- potential health hazards, and
- safety precautions which shall be taken.

C.8. Station Manager Responsibilities. The Station Manager, with assistance of the site Safety or Environmental/Safety Focal Point, shall ensure that each employee has a basic knowledge of the information contained in MSDS and an understanding of proper use of that information. The Station Manager shall ensure:

- MSDSs are available to employees in their work areas during each work shift, and
- MSDS information is provided for each hazardous chemical.

C.9. Employee Responsibilities. Successful implementation of the Hazard Communication Program depends on active involvement of personnel at the field office or Operating Unit. Every NWS employee who purchases, handles, or uses hazardous chemical products is responsible:

- a. To know where to get information about the hazardous chemical labels used in the work area;
- b. To read and understand the information on hazardous chemical labels and MSDS;
- c. To keep the work area clean;
- d. To use protective clothing and equipment, as required;
- e. Not to smoke, eat, or drink around hazardous chemicals;
- f. To learn the emergency procedures for the work area;
- g. To follow the procedures for hazardous chemical disposal and spill cleanup;
- h. To practice safe work habits; and
- i. To attend required training.

C.10. On-site Contractors. When soliciting a contract, it is the Contracting Officer's Technical Representative (COTR) responsibility to inform the Contracting Officer of any possible hazards associated with work on a contract, so that notification and special conditions can be put into the solicitation prior to contract award. The site Safety or Environmental/Safety Focal Point shall advise the COTR of possible hazards that contractor employees encounter while working at an NWS facility. Contractors working at the field office or Operating Unit shall comply with the state of _____ occupational safety and health regulations.
state (or no entry if state does not have an OSHA approved plan)

(Federal employees on the federal property are not governed by state OSHA).

The Contracting Officer shall obtain from a contractor a list of all chemicals the contractor intends to bring into or on to the work area (interior/exterior paint, sealants, tile or carpet adhesives, cleaning supplies, fertilizers, etc.). This includes construction as well as janitorial and landscaping contracts. A copy of the MSDS(s) shall be provided to the COTR and the Safety or Environmental/Safety Focal Point. MSDS(s) shall be posted in the work area, so that all employees affected by the contract work can have an access to them. If any engineering controls (ventilation, etc.) are required, the contractor shall describe the method(s) that shall be used to implement these controls and a work schedule for the implementation. This information should be posted or otherwise communicated to affected personnel.

Upon notification by the COTR, the Safety or Environmental/Safety Focal Point shall advise outside contractor employees of any hazards that they may encounter at NWS facilities. Contractor employees shall be informed about the location of this Hazard Communication Program and the availability of MSDS(s). The information provided by the Government shall be sufficient to enable the contractor to satisfy his own Hazard Communication Program responsibilities as promulgated by the _____ State OSHA-approved plan (if applicable).
state (or no entry if state does not have an OSHA approved plan)

In addition, the COTR shall ensure that contractor personnel have received Hazard Communication training in accordance with the Federal and state OSHA requirements (as applicable).

SECTION D
Worksite Hazardous Chemical List

Site/Location: _____ Region: _____

Address: _____

The following is a master chemical list of all known hazardous chemicals used at this facility. Further information on each noted chemical can be obtained by reviewing the worksite Material Safety Data Sheets (MSDS).

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation/ Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location

SECTION E

Worksite Material Safety Data Sheets

The Safety or Environmental/Safety Focal Point shall maintain a complete and accurate set of material safety data sheets (MSDS) for all hazardous chemicals included in the hazardous chemical list. A master MSDS set shall be maintained at the Weather Forecast Office (WFO) or WFO/River Forecast Center (RFC). In addition, uniquely defined sets shall be maintained and updated for:

- Radar Data Acquisition (RDA),
- Upper Air Inflation Building (UAIB) and/or Balloon Inflation Launching System (BILS),
- Automated Surface Observing System (ASOS),
- NOAA Weather Radio,
- cooperative stations,
- Transition Power Maintenance Shelter (TPMS),
- storage sites,
- housing, and
- other sites associated with the WFO or WFO/RFC.

MSDS(s) may be obtained through the manufacturer, shipping documents, NLSC, or from a web site such as: <http://www.hazard.com> or from the set of MSDSs compiled by the Contractor (EG&G).

SECTION F

Labeling Information

Chemical warning labels may include the following information:

Identity of the Chemical - product name, chemical name, or trade name

Signal Word - stating the degree of hazard, such as “**Caution!**”, “**Warning!**” or “**Danger!**”

Hazard Statement - stating the major hazards, such as: “**extremely flammable**”, “**explosive**”, “**corrosive**”, or **harmful if inhaled**”

Precautions - what to do to avoid injury or illness, such as: “**acute breathing vapors**” or “**wash thoroughly after handling**”

Instructions in Case of Exposure - first aid information for exposure to the chemical(s).

Fire, Spill, or Leak Instructions - how to put out or control fires and clean up leaks or spills.

Handling and Storage Instructions - special procedures for handling and storing chemical containers.

Antidotes - measures that can be used by medical personnel to counteract the effects of chemical exposure.

Notes to Physician - information for physician concerning exposure to the chemical(s).

Disposal Instructions - special disposal instructions may be provided on the label; however, follow state and local disposal requirements.

Examples of standard labels are found on the following pages.

HAZARDOUS CHEMICAL WARNING LABEL					
1. CHEMICAL/COMMON NAME					
2. HAZARD CODE		3. NSN/LSN			
4. PART NUMBER					
5. ITEM NAME					
7. HAZARDS <i>(X ALL THAT APPLY)</i>	<div style="display: flex; justify-content: space-between;"> ▲ (1) Acute <i>(Immediate)</i> (2) Chronic <i>(Delayed)</i> </div>				
	NONE	SLIGHT	MODERATE	SEVERE	
a. HEALTH					
b. CONTACT					
c. FIRE					
d. REACTIVITY					
7. SPECIFIC HAZARDS AND PRECAUTIONS (Including Target Organ Effects) <p style="text-align: center;"><i>(See MSDS for further information)</i></p>					
8. PROTECT <i>(X all that apply)</i>		a. EYES		b. SKIN	C. RESPIRATORY
9. CONTACT: a. COMPANY NAME					
b. ADDRESS <i>(Street, P.O. Box, City, State, Zip Code and Country)</i>					
c. EMERGENCY TELEPHONE NUMBER <i>(Include Area Code)</i>					
10. PROCUREMENT YEAR FOR HAZARDOUS CHEMICAL					

National Fire Protection Agency (NFPA) 704 Warning Diamond

BLUE = TOXICITY

	4	3	2	1
ORAL				
mg/kg	<5	5-50	50-500	500-2,000
DERM				
mg/kg	<40	40-200	200-1,000	1,000-2,000
inhl				
MG/KG	<0.05	0.5-2	2-10	10-200
idhl	1,000	1,000-3,000	3,000-5,000	5,000-10,000

Definition Short term exposure results in:
 Death Serious acute injury or perm. eye damage
 If exp. is intense, temp. incapac.


RED=FLAMMABILITY

	4	3	2	1
Flash Point	<73 °F	73-100 °F	100-200	>200 °F
· Flam. Gas at STP				
· Liquids under pressure				
· Ignites in air at STP			· Liquid or solid	
· Ignites at STP				
· Expl. in air.		· Require mod. heating		
· Dusts, fibers		· Require lots of heating		
Boiling Point	<100 °F	>100 °F		

Red

YELLOW = REACTIVITY

- 4 May detonate at STP
- 3 Explosive (requires detonation)
- 2 Unstable (reacts with water)
- 1 Normally stable, decomposes



Any exp. leads to irritation

B

Blue
WHITE = OTHER HAZARDS

- OX Oxidizer
- W Water Reactive
- Radioactive
- COR Corrosive
- ACD Acid
- AKL Alkali

SECTION G

Work Site Training Records

SITE NAME: _____



enter name of site, location

HAZARD COMMUNICATION TRAINING RECORD

This certifies that

Employee name

has received Hazard Communication Training as described in the Hazard Communication Program. The training was conducted on _____

date

Instructor's signature

I understand the Hazard Communication Standard requirements and know where the written NWS Hazard Communication Program is located. I will perform my job in compliance with instructions contained herein.

Employee signature

date

SECTION H

NWS Hazardous Chemical List Requirements

H.1 How to Identify Hazardous Chemicals. The responsibility for determining whether a chemical is hazardous lies with the chemical manufacturer or importer of a chemical. The chemical manufacturer or importer shall pass this information to their customers. As a user of chemicals, NWS employees have to rely on the evaluation received from these suppliers through labels on containers and material safety data sheets (MSDS). To prepare a list of the chemicals at the work site, the site shall be surveyed and the names of chemicals that have a label indicating a potential hazard shall be written down (e.g., “Flammable” or “causes skin irritation”) or look for words such as: DANGER, WARNING, CAUTION, or HARMFUL on the warning label. Personnel involved in surveying the site shall also be aware of hazardous substances that are not enclosed in containers and that are generated during work operations (e.g., soldering or welding fumes, dusts, etc.) or in normal administrative tasks (e.g., copier toner, printer cartridges, or pen inks).

Check whether any of the chemicals identified during the survey are listed in the following publications:

- Title 29 Code of Federal Regulations (CFR) Part 1910, Subpart Z, Toxic and Hazardous Substances;
- The American Conference of Government Industrial Hygienists (ACGIH) latest edition of Threshold Limit Values for Chemical Substances and Physical Agents in the Work Environment; and
- The latest edition of the Annual Report on Carcinogens for suspected or confirmed carcinogens by the National Toxicology Program, or the International Agency for Research on Cancer (IARC) in the latest edition of their IARC monographs.

The Occupational Safety and Health Administration (OSHA) provides interpretations of the Act and the Hazard Communication Standard for various products, based upon users’ requests. The letters requesting information and corresponding interpretations can be found on the Internet at http://www.osha-slc.gov/OSHDoc/toc_interps.html

Once the hazardous chemicals list is completed, it shall be reviewed to determine if any of the materials or chemicals are exempted by 29 CFR Part 1910.1200 paragraph (b)(6). For example, rubbing alcohol maintained at a first-aid station would be exempt under paragraph (b)(6)(vi) of the 29 CFR 1910.1200 standard because it is intended for personal use by employees. To be prudent, some employers include all chemicals even if they are exempted. In general, if there is any question regarding a particular chemical, it is best to include that chemical in the hazardous chemical list. The listing shall include all chemicals at the work site rather than rely on the exemption rule.

H.2 How to List Chemicals in the Workplace. All hazardous chemicals known to be present in the workplace shall be listed, using an identifier that appears on the appropriate MSDS and on label for the chemical. The list may also include common or trade names, Chemical Abstract Service (CAS) Registry numbers, etc. See Section D for NWS Hazardous Chemicals List requirements. The master list shall be compiled for the entire workplace and shall include the lists developed for individual buildings associated with the facility. This master list is designed to be an inventory of all items for which an MSDS shall be obtained. It shall be a part of the written Hazard Communication program and shall be available to employees upon their request. The following list identifies most common types of potentially hazardous chemicals and chemical products that may be present at the work site:

Acids	Gasoline
Adhesives	Glues
Aerosols	Greases
Asbestos	Industrial oils
Batteries	Inks
Battery fluids	Insecticides
Benzene	Janitorial supplies
Catalysts	Kerosene
Caustics	Lacquers
Cleaning agents	Lead
Cool tar pitch	Lye
Coatings	Metals and welding rods used in welding
Compressed gases such as hydrogen, propane, oxygen, etc.	Oxalic acid
Copier toner (only for those who service the copier)	Paints
Degreasing agents	Pesticides
Detergents	Plastics
Dusts	Process chemicals
Etching agents	Resins
Fiberglass	Sealers
Flammables	Shellacs
Foaming resins	Solders
Fuels	Solvents

Strippers

Surfactants Varnishes

Wood preservatives

Xylene

Thinners

Interpreted as Exempt, under 29 CFR 1910.1200 (b)(6)(iv)

“white out”

most office products (pens, pencils, adhesive tape)

copier toner - for those who use the copier intermittently

Typical NWS Hazardous Chemical Products

helium

hydrogen

oxygen

propane

acetylene

mercury

potassium hydroxide

lead acid batteries

AFOS toner

solvents

gasoline

lubrication oils and greases

diesel fuel

dielectric oil

paints

SECTION I

Material Safety Data Sheets Requirements

I.1 Introduction. The Material Safety Data Sheet (MSDS) is a detailed information bulletin prepared by the manufacturer or importer of a chemical that describes the physical and chemical properties, physical and health hazards, routes of exposure, precautions for safe handling, and use, emergency and first aid procedures, and control measures. Information presented in an MSDS can assist in the selection of safe products and can help to prepare employers and employees to respond effectively to daily exposure situations as well as to emergency situations.

MSDSs are a comprehensive source of information for all types of employers. There may be information on the MSDS that is not useful or important in your particular operations. Concentrate on the applicable portions. Generally, hazard information and protective measures shall be the focus of concern.

I.2 OSHA Requirements. Chemical product buyers are entitled to obtain MSDS automatically upon the purchase of the material. When new and significant information concerning a product's hazards or ways to protect against the hazards becomes available, chemical manufacturers, importers, or distributors shall add it to their MSDS within three (3) months and provide it to their customers with the next shipment. Station managers shall ensure that MSDSs for each hazardous chemical used in the workplace are available. If there are multiple suppliers of the same chemical, there is no need to retain multiple MSDSs for that chemical.

I.3 Shipments. While MSDSs are not required to be physically attached to a shipment, they shall accompany or precede the shipment. When the manufacturer/supplier fails to send an MSDS with a shipment labeled as hazardous chemical, the ordering employee shall obtain one from the chemical manufacturer, importer, or distributor as soon as possible. Similarly, if the MSDS is incomplete or unclear, the Safety or Environmental/Safety Focal Point shall contact the manufacturer or importer to obtain clarification or missing information. Section J provides a sample letter for requesting an MSDS or additional information.

I.4 Obtaining MSDS. When the Safety or Environmental/Safety Focal Point is unable to obtain an MSDS from a supplier or manufacturer, he/she shall submit a formal written complaint to the nearest OSHA area office.

I.5 Sections of an MSDS. OSHA specifies the information to be included on an MSDS, but does not provide the precise format. OSHA developed a non-mandatory OSHA Form 174, included in this section that meets MSDS requirements. The MSDS shall be in English and, at a minimum, include the following information:

- a. Section I Chemical Identity
- b. Section II Hazardous Ingredients
- c. Section III Physical and Chemical Characteristics

- d. Section IV Fire and Explosion Hazard Data
- e. Section V Reactivity Data
- f. Section VI Health Hazards
- g. Section VII Precautions for Safe Handling and Use
- h. Section VIII Control Measures

I.5.1 Section I - Chemical Identity. The chemical and common name(s) for single chemical substances. The identify on the MSDS shall reflect the name on the label.

I.5.2 Section II - Hazardous Ingredients:

- For a hazardous chemical mixture that has been tested as a whole to determine its hazards, the chemical and common names of the ingredients that are associated with the hazards and the common name of the mixture shall be listed (for hazardous chemical mixtures that have been tested as a whole);
- chemical and common names of all ingredients determined to be health hazards and comprising 1 percent (1%) or greater of the mixture shall be listed (for hazardous chemical mixtures that have not been tested as a whole);
- chemical and common names of carcinogens shall be listed if they are present in the mixture at levels of 0.1 percent (0.1%) or greater;
- all components of a mixture that have been determined to present a physical hazard shall be listed; and
- chemical and common names of all ingredients determined to be health hazards and comprising less than 1 percent (0.1 percent for carcinogens) of the mixture shall also be listed if they can exceed established the Permissible Exposure Limit (PEL) or Threshold Limit Value (TLV) or present a health risk to exposed employees in these concentrations.

I.5.3 Section III Physical and Chemical Characteristics. The physical and chemical characteristics of the hazardous substance shall be listed. These include such items as boiling and freezing points, density, vapor pressure, specific gravity, solubility, volatility, and the product's general appearance and odor. These characteristics provide important information for designing safe and healthful work practices.

I.5.4 Section IV Fire and Explosion Hazard Data. The compound's potential for fire and explosion shall be described. Also, the fire hazards of the chemical and the conditions under which it could ignite or explode shall be identified. Recommended extinguishing agents and fire fighting methods shall be described.

I.5.5 Section V Reactivity Data. This section shall include information about other chemicals and substances with which the chemical is incompatible, or with which it reacts. Information on any hazardous decomposition products, such as carbon monoxide, shall be included.

I.5.6 Section VI Health Hazards. The acute and chronic health hazards of the chemical, together with the signs and symptoms of exposure, shall be listed. In addition, any medical conditions that are aggravated by exposure to the compound shall be included. Specific types of chemical health hazards are defined in the standard and include carcinogens, corrosives, toxins, irritants, sensitizers, mutagens, teratogens, and effects on target organs (liver, kidney, nervous system, blood, lungs, mucous membranes, reproductive system, skin, eyes, etc.).

The primary route of entry shall be described in this section. Three principal routes are: inhalation, skin absorption, and ingestion.

The OSHA PEL, American Conference of Governmental Industrial Hygienists (ACGIH) TLV, and other exposure levels used or recommended by the chemical manufacturer.

This section shall indicate whether the compound is listed as a carcinogen (cancer causing agent) by OSHA, the National Toxicology Program (NTP) or the International Agency for Research on Cancer (IARC).

I.5.7 Section VII Precautions for Safe Handling and Use. Precautions for safe handling and use. Include recommended industrial hygiene practices, precautions to be taken during repair and maintenance of equipment, and procedures for cleaning up spills and leaks. Some manufacturers also use this section to include additional information such as the Environmental Protection Agency (EPA), state, and local requirements.

I.5.8. Section VIII Control Measures. Control measures include engineering controls (ventilation), safe handling procedures, and personal protective equipment. Information often includes the use of goggles, gloves, body suits, respirators, and face shields.

I.6 Material Safety Data Sheet Checklist. The Safety or Environmental/Safety Focal Point shall ensure that each MSDS contains all the required information on this checklist:

1. Product or chemical identity used on the label. _____
2. Manufacturer's name, address, and phone number. _____
3. Chemical and common names of each hazardous ingredient. _____
4. If the product includes a trade secret component, an emergency number and secret ID are available for the product and trade secret components. _____
5. Preparation or revision date. _____
6. Hazardous chemical's physical and chemical characteristics, such as vapor pressure and flashpoint. _____
7. Physical hazards, including the potential for fire, explosion, and reactivity. _____
8. Known health hazards. _____
9. OSHA permissible exposure limit (PEL), ACGIH threshold limit (TLV) or other _____

- exposure limits. —
- 10. Emergency and first aid procedures. —
- 11. Whether OSHA, NTP, or IARC lists the ingredient(s) as a carcinogen. —
- 12. Precautions for safe handling and use. —
- 13. Control measures such as engineering controls, work practices, hygienic practices
or personal protective equipment. —
- 14. Primary routes of entry. —
- 15. Procedures for spills, leaks, and clean up. —
- 17. Department of Transportation (DOT) shipping name and hazard class. —

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard shall be consulted for specific requirements.



U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

IDENTITY (*As Used on Label and List*)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space shall be marked to indicate that.

Section I

Manufacturer's Name	Emergency Telephone Number
Address (<i>Number, Street, City, State, and Zip Code</i>)	Telephone Number for Information
	Date Prepared
	Signature of Preparer (<i>optional</i>)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s)) TLV Recommended % (<i>optional</i>)	Other Limits OSHA PEL ACGIH

Section III - Physical/Chemical Characteristics

Boiling Point	Specific Gravity (H ₂ O = 1)

Vapor Pressure (mm Hg)	Melting Point
Vapor Density (AIR = 1)	Evaporation Rate (Butyl Acetate = 1)

Solubility in Water

Appearance and Odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
---------------------------	------------------	-----	-----

Extinguishing Media

Special Fire Fighting Procedures

Unusual Fire and Explosion Hazards

(Reproduce Locally)
Sept. 1985

OSHA 174,

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable		

Incompatibility (*Materials to Avoid*)

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur		

Section VI - Health Hazard Data

Route(s) of Entry	Information?	Skin?
-------------------	--------------	-------

Health Hazards (*Acute and Chronic*)

Carcinogenicity OSHA Regulations?	NTP?	IARC Monographs?
--------------------------------------	------	------------------

Signs and Symptoms of Exposure

Medical Conditions

Generally Aggravated by Exposure

Emergency and First Aid Procedures

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case of Material is Released or Spilled

Waste Disposal Method

Precautions to Be Taken in Handling or Storing

Other Precautions

Section VIII - Control Measures

Respiratory Protection (*Specify Type*)

Ventilation	Local Exhaust	Special
	Mechanical (<i>General</i>)	Other

Protective Gloves

Other Protective Clothing or Equipment	Eye Protection
--	----------------

Notice of Alleged Safety or Health Hazards

U.S. Department of Labor

Occupational Safety and Health Administration

Form Approved

For the General Public:

O.M.B. No. 1218-0064

This form is provided for the assistance of any complainant and is not intended to constitute the exclusive means by which a complaint may be registered with the U.S. Department of Labor.

Section 8(f)(I) of the Williams-Steiger Occupational Safety and Health Act, 29 U.S.C. 651, provides as follows: Any employees or representative of employees who believe that a violation of a safety or health standard exists that threatens physical harm, or that an imminent danger exists, may request an inspection by giving notice to the Secretary or his authorized representative of such violation or danger. Any such notice shall be reduced to writing, shall set forth with reasonable particularity the grounds for the notice, and shall be signed by the employees or representative of employees, and a copy shall be provided the employer or his agent no later than at the time of inspection, except that, upon request of the person giving such notice, his name and the names of individual employees referred t therein shall not appear in such copy or on any record published, released, or made available pursuant to subsection (g) of this section. If upon receipt of such notification, the Secretary determines there are reasonable grounds to believe that such violation or danger exists, he shall make a special inspection in accordance with the provisions of this section as soon as practicable to determine if such violation or danger exists. If the Secretary determines there are no reasonable grounds to believe that a violation or danger exists, he shall notify the employees or employee representative of the employees in writing of such a determination.

NOTE: Section 11 of the Act provides explicit protection for employees exercising their rights, including making safety and health complaints.

For Federal Employees:

This report format is provided to assist Federal employees or authorized representatives in registering a report of unsafe or unhealthful working conditions with the U.S. Department of Labor.

The Secretary of Labor may conduct unannounced inspections of agency workplaces when deemed necessary if an agency does not have occupational safety and health committees established in accordance with Subpart F, 29 CFR Part 1960; or in response to reports of unsafe or unhealthful working conditions upon request of such agency committees under Sec. 1-3, Executive Order 12196; or in the case of a report of imminent danger when such a committee has not responded to the report as required in Sec. 1-201(h).

INSTRUCTIONS:

Open the form and complete items 2 through 18 as accurately and completely as possible. Describe each hazard you think exists in as much detail as you can. If the hazards described in your complaint are not all in the same area, please identify where each hazard can be found at the worksite. If there is any particular evidence that supports your suspicion that a hazard exists (for instance, a recent accident or physical symptoms of employees at your site) include the information in your description. If you need more space than is provided on the form, continue on any other sheet of paper.

After you have completed the form, return it to your local OSHA office.

NOTE: It is unlawful to make any false statement, representation or certification in any document filed pursuant to the Occupational Safety and Health Act of 1970. Violations can be punished by a fine of not more than \$70,000, or imprisonment of not more than six months, or by both. (Section 17(g))

OSHA-7 (Rev 1/90)

Notice of Alleged Safety or Health Hazards

U.S. Department of Labor

Occupational Safety and Health

Administration

MOD	Date	1. Complaint Number
-----	------	---------------------

2. Employer Name

3. State Location (Street, City, State, Zip)

4. Mailing Address (If different) (Street, City, State, Zip)

5. Management Official

7. Telephone

7. Type of Business

8. Hazard Description. Describe briefly the hazard(s) which you believe exist. Include the approximate number of employees exposed to or threatened by each hazard.

9. Hazard Location *Specify the particular building or worksite where the alleged violation exists.*

NWSM 50-1115 SEPTEMBER 15, 2009

10. Has this condition been brought to the attention of (Mark "X" in all that apply)					
<input type="checkbox"/> Employer <input type="checkbox"/> Other Government Agency					
11. Please indicate your desire					
<input type="checkbox"/> Do not reveal my name to the Employer <input type="checkbox"/> My name may be revealed to the Employer					
12. The Undersigned (Mark "X" in one box)					
<input type="checkbox"/> Employer		<input type="checkbox"/> Federal Safety and Health Committee			
<input type="checkbox"/> Representative of Employees		<input type="checkbox"/> Other (specify)			
believes that a violation of an Occupational Safety or Health standard exists which is a job safety or health hazard at the establishment named on this form.					
13. Complainant Name (Type or print name)				14. Telephone Number	
15. Address (Address, City, State, ZIP)					
17. Signature				17. Date	
18. If you are an authorized representative of employees affected by this complaint, please state the name of the organization that you represent and your					
Organization Name			Your Title		
OFFICIAL USE ONLY					
19. Reporting ID	20. Previous Activity? <input type="checkbox"/> Yes <input type="checkbox"/> No If yes, enter Type Number				21. Optional complaint Number
Identification	22. Establishment Name Change? <input type="checkbox"/>	23. Site Address Change? <input type="checkbox"/>	24. Employer ID (State's Option)		25. City Code
Receipt Information	27. Received by	28. Send OSHA-7? <input type="checkbox"/> Yes <input type="checkbox"/> No	29. Date	30. Time AM PM	31. Supervisor (s) Assigned
					a.
Complaint Evaluation	34. Evaluated by			35. Subject and Severity Discrimination <input type="checkbox"/>	

	<p>37. Is this a Valid Complaint? <input type="checkbox"/> Yes <input type="checkbox"/> No</p> <p>37. Formality <input type="checkbox"/> Formal <input type="checkbox"/> Non-formal</p> <p>38. <input type="checkbox"/> Migrant Farm Worker</p>	<p>Imminent</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>Danger</td> <td>Serious</td> <td>Other</td> </tr> <tr> <td>Safety</td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> <tr> <td>Health</td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> </table>		Danger	Serious	Other	Safety	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Health	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	Danger	Serious	Other											
Safety	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>											
Health	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>											
Complaint Action	<p>39. Send Letter</p> <p>a. <input type="checkbox"/> No inspection - for Invalid Complaints</p> <p style="margin-left: 40px;"><input type="checkbox"/> Too Vague or Unsubstantiated</p> <p style="margin-left: 40px;"><input type="checkbox"/> Recent Inspection or Objective Evidence (Date of Inspection)</p> <p style="margin-left: 40px;"><input type="checkbox"/> Not in OSHA's Jurisdiction</p> <p>b. <input type="checkbox"/> No Inspection - for Non-formal Complaints</p> <p style="margin-left: 40px;"><input type="checkbox"/> No Imminent Danger or No Standard</p> <p style="margin-left: 40px;"><input type="checkbox"/> No Direct Relation to S&H</p> <p style="margin-left: 40px;"><input type="checkbox"/> Not Enough Information To Evaluate</p>													
47. Optional Information														
Type	ID	Value	Type	ID	Value									
<p><input type="checkbox"/> 48. Close Complaint</p>														
48. Comments:														

SECTION J

NWS Material Safety Data Sheet Request

SAMPLE LETTER REQUESTING AN MSDS

Weather Forecast Office
National Weather Service

City, State, Zip Code

Blitz Manufacturing Company
1923 Oak Grove Lane
Springfield, Massachusetts 02110

Gentlemen:

The Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) requires employers to obtain material safety data sheets (MSDS) for all hazardous substances used in their facility, and to make these MSDS(s) available to employees potentially exposed to these hazardous substances.

We request a copy of the MSDS for your product listed as Part/Stock Number _____ We did not receive an MSDS with the initial shipment of the _____ (list the product name) delivered to us on _____ (specify date). We also request any additional information, supplementing the MSDS, or any other relevant data that your company or supplier has concerning the safety and health aspects of using this product.

Please consider this letter as a standing request to your company for any information concerning the safety and health aspects of using this product that may become known in the future. The MSDS and any other relevant information shall be sent to us within 10, 20, 30 days (select appropriate time). Delays in receiving the MSDS information may prevent use of your product. Please send the requested information to:

Mr./Mrs./Ms. _____

Safety or Environmental/Safety Focal Point

Street Address _____

City, State Zip Code _____

NWSM 50-1115 SEPTEMBER 15, 2009

Please be advised that if we do not receive the MSDS on the above chemical by _____(date), we shall notify OSHA of our inability to obtain this information. It is our intent to comply with all provisions of the Hazard Communication Standard (1910.1200). Availability of MSDS(s) is integral to this effort.

Your cooperation is greatly appreciated. Thank you for your timely response to this request. If you have any questions concerning this matter, please contact Mr./Mrs./Ms. _____
at () _____ - _____

Sincerely,

Safety or Environmental/Safety Focal Point

**SAMPLE LETTER REQUESTING
ADDITIONAL INFORMATION ON MSDS**

Weather Forecast Office
National Weather Service

Street Address

City, State, Zip Code

ACE Chemical Company, Incorporated
214 Capitol Drive
Richmond, Virginia 23230

Dear Mr. Winston:

In an effort to comply with the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard set forth in 29 CFR 1910.1200, the National Weather Service is seeking additional information on a chemical produced by ACE Chemical Company. The material safety data sheets (MSDS) forwarded to us appear to be deficient in the following:

1. Clear-VU 210 - no health effects listed.
2. Cleanup 34 - Solvent - no physical hazard listed.

Please be advised that in order to comply with the Hazard Communication Standard and to provide adequate training for our employees, we shall have complete MSDSs, particularly for the above-named items. Thank you for timely response to this request. Your cooperation is greatly appreciated.

Sincerely,

Safety or Environmental/Safety Focal Point

MSDS REQUEST FILE

Date Sent	Date Received	Chemical Name	Location(s)				
			WFO	WFO/ RFC	RDA	TPMS	UAIB

SECTION K
Training Program

K.1 Introduction. Training is an integral part of the Hazard Communication Program. NWS employees need to know about the hazardous materials and chemicals with which they work. They need to know whether these materials and chemicals present a risk to their safety or health, and how to minimize or eliminate such risks.

The Station Manager shall ensure that all employees receive initial Hazard Communication training and re-training, as appropriate. The following are available and recommended training resources.

K.1.1 Available Training Resources

- 3-Day Environmental Compliance with OSHA Overview Course. This course is available for the station Environmental and Safety Focal Points. It includes a section on the OSHA Hazard Communication Standard. Upon completion of the course, the Safety and Environmental/Safety Focal Points shall be able to develop the site-specific written Hazard Communication Program as well as arrange OSHA-mandated training of site personnel.
- 2-Day Refresher Environmental Compliance with OSHA Overview Course
- Video Tape, Right-to-Know Update (21 minutes). The video tapes have been purchased by NWS Headquarters Safety Office and distributed to NWS sites. The tape describes the Hazard Communication Program, MSDS, hazards of workplace chemicals, protective measures, and accident procedures and first aid.

K.1.2 Additional Training Resources

- Coastal Video Communications Corporation. Clarity Media of Coastal Video Communications Corporation developed CD-ROM training materials on the Hazard Communication Standard. The CD-ROM can be purchased through a Government Services Agency (GSA) contract number GS-02F-9309C (9/99) at:

Coastal Video Communications Corporation

3083 Brickhouse Course

Virginia Beach, Virginia 23452-9942

804-498-9014 or 800-767-7703

FAX: 804-498-3657

e-mail: sales@coastal.com

The CD-ROM Hazard Communication Course requires the following to operate:

Pentium PC

Small Computer System Interface (SCSI) 2 Hard Drive with 112 MB of free space

32-bit PCI bus slot operating at 33MHz

Super Video Graphics Adapter (SVGA) card

One free serial port

Windows 3.11 or later

DOS 7.0 or later

- Federal Government Hazard Communication Training Program. The Federal Government Hazard Communication Training Program provides excellent resources to help in complying with training requirements of the Hazard Communication Standard. The program includes:
 - The Federal Hazard Communication Training Program, Trainer's Guide;
 - The Federal Hazard Communication Training Program, Student's Workbook; and
 - 90 minute videotape.

Copies of this technical program can be obtained from:

National Technical Information Service (NTIS)

5285 Port Royal Road

Springfield, Virginia 22161

NTIS No. AVA 17251KK00

Sales Desk: (703) 487-4650 8:30 am - 5:00 pm, Eastern time

This training course may be provided by an instructor in a classroom environment or as a self-study. The student workbook contains easy-to-follow directions and applicable exercises. The course includes all training sections required by the Standard. It consists of the following seven lessons:

- Lesson 1: The Federal Hazard Communication Standard

This lesson provides an introduction to the Standard issued by the Occupational Safety and Health Act, as it applies to Federal agencies. It identifies the goals of the Hazard Communication Standard and describes each of the actions required.

- Lesson 2: Chemical Forms and Exposure Hazards

This lesson describes various forms of chemical materials. It helps to recognize potential sources of exposure to chemicals in the workplace. It also describes how chemicals can enter the body when exposure occurs.

- Lesson 3: Types of Physical and Health Hazards

Chemical materials can present physical and/or health hazards. This lesson describes specific types of chemical hazards in each category and helps in understanding the risks associated with each type of hazard.

- Lesson 4: Controlling Chemical Hazards

This lesson introduces the ways in which chemical hazards can be controlled. It describes engineering/mechanical controls, types of personal protective equipment, and various administrative/procedural controls. It tells about ways to detect uncontrolled chemical hazards in the workplace and what to do about them.

- Lesson 5: Introduction to MSDS and MSDS Physical Hazard Information.

Material Safety Data Sheets (MSDS) are required by law to identify chemical materials, describe important physical properties, known hazards, and required controls. This lesson shows how to use those sections of the MSDS that identify chemical materials, physical properties, physical hazards, ways of controlling physical hazards, and correct procedures to follow if a fire, spill, or leak occurs.

- Lesson 6: MSDS Health Hazard Information

This lesson shows how to use information on the MSDS describing health hazards and protective equipment required to guard against hazard exposure. It also covers special precautions given on the MSDS, such as correct procedures for safe material handling and storage.

- Lesson 7: Using Labels and The Hazardous Chemical List.

The Hazard Communication Standard requires every workplace to use warning labels and maintain a Hazardous Chemicals List. This lesson identifies the information that these resources shall contain and shows how to use these documents to provide protection from chemical hazards.

Additionally, NWS training shall include information on how to report leaks and spills and which entities shall be notified if a spill occurs (e.g., local fire department, local emergency planning commission, National Response Center, etc.). This is applicable to diesel oil spills, big mercury spills (broken barometers), etc. (See Section L)

K.2 Training Checklist.

	<u>Complete</u>	<u>Incomplete</u>
1. Establish Hazard Communication training program.	_____	_____
2. Identify employees who need training.	_____	_____
3. Establish training program that ensures new employees are informed and trained at the time of their initial assignment and whenever new hazards are introduced.	_____	_____
4. Inform employees of the requirements of the Hazard Communication standard.	_____	_____
5. Inform employees of the location and availability of the written Hazard Communication Program, including the	_____	_____

K.2 Training Checklist.

	<u>Complete</u>	<u>Incomplete</u>
required list(s) of hazardous chemicals and Material Safety Data Sheets (MSDS).		
7. Inform employees of any operations in their work areas where hazardous chemicals are present.	_____	_____
7. Train employees about the measures that can be used to protect them from the chemical hazards.	_____	_____
8. Train employees about the physical and health hazards of the chemicals in the work area.	_____	_____
9. Train employees about the methods to detect the presence or release of hazardous chemicals in the workplace.	_____	_____
10. Train employees in the use of proper work practices, personal protective equipment and clothing, and other controls to reduce or eliminate their exposure to the chemicals in their work areas.	_____	_____
11. Train employees in emergency and first aid procedures and signs of overexposure.	_____	_____
12. Train employees to understand labeling system and MSDS and how to obtain and use the appropriate hazard information.	_____	_____
13. Establish procedures to ensure proper labeling for containers that hold hazardous chemicals.	_____	_____
14. Establish procedures to identify and inform employees of new hazardous chemicals before they are introduced into a work area.	_____	_____
15. Establish a way to inform employees of new hazards associated with the chemicals they already use.	_____	_____
16. Establish a procedure to train employees involved in performing hazardous non-routine tasks (e.g., confined space entry, etc.).	_____	_____
17. Establish procedures to evaluate the effectiveness of the training program and to keep track of personnel training.	_____	_____

SECTION L

Cleanup and Disposal of Typical Hazardous Materials and Wastes

L.1 Hazardous Materials Used in the National Weather Service:

The following is the list of hazardous materials typically used by NWS personnel:

- hydrogen (for balloon launching),
- potassium hydroxide (for hydrogen generators),
- mercury (applicable to barometers, thermostats, mercury switches, rotary joints),
- printer plotter module (PPM) toner/dispersant [Automation of Field Operations and Services (AFOS)],
- lead acid, mercury-oxide, and other batteries,
- propylene glycol when contaminated by oil (for precipitation gages),
- dielectric oil (for doppler weather surveillance radar, WSR-88D),
- solvents and degreasers,
- diesel fuel,
- paints, and
- cleaners.

The above listed hazardous materials have a potential for release during routine NWS operations. A release is defined as any spilling, leaking, pumping, emitting, emptying, discharging, injection, escaping, leaching, dumping, or disposing into the environment. The term excludes release of nuclear materials and normal application of fertilizers.

L.2 Material Safety Data Sheets (MSDS)

Material safety data sheets (MSDS) for most of hazardous materials utilized by NWS personnel acquired through the Consolidated Logistics System (CLS) are available at the National Logistics Support Center (NLSC). When ordering an item, the Safety and Environmental/Safety Focal Point shall request an MSDS unless it is already available at the site.

If any chemical product or item containing a chemical is purchased at a local specialty store, the purchaser shall ask the vendor for the MSDS. The instructions specified in the written NWS Hazard Communication Program shall be followed. Certain items in stock at NLSC are identified as potentially hazardous to human health; however, they are not assigned hazardous codes in CLS. Currently, hazardous material codes in CLS are based upon Department of Transportation classifications. Changes are proposed which include health and other environmental hazard codes. A book of MSDS(s) for items in the CLS system shall be available in the future for NWS field personnel. It is good operational practice to obtain MSDS even for the items that do not display typical hazardous characteristics, but may present health hazards.

L.3 Small Spill Cleanup (General guidelines). The following are general steps for NWS personnel to minimize the hazards generated by a small spill of hazardous or potentially hazardous substances:

- evaluation,
- site security,
- notification,
- personal protective equipment,
- controlling the spill,
- containing the spill,
- clean up,
- waste transportation.

Each of the above steps is composed of subsections that are described below. A thorough pre-planning is necessary to ensure a safe response to hazardous materials spills.

L.3.1 Evaluation. The process of evaluation allows the situation to be sized up and the most *immediate hazard* to be identified. The following steps shall be followed:

- Identify spill “transportation” mechanism.

Spill “transportation” mechanisms are routes by which the spilled material shall move. These routes may include drains, sumps, channels, ducts, and exposed soils. Consider the physical/chemical properties of the material that has been released. For instance, if the spill is a powdered material, a breeze might create a hazardous dust as particles become airborne. Liquids and heavier than air gases will tend to flow along low areas. Lighter than air gases will dissipate unless weather conditions or obstructions (such as buildings) prevent the escape of the gas.

- Identify labeling, container’s material and condition, or other relevant information.

Look for labels, especially Department of Transportation (DOT) warning labels or National Fire Protection Association (NFPA) 704 Warning Diamonds.

Note the type and construction material of the container (e.g., open head, steel 55-gallon drum or tight head polypropylene 5-gallon can).

If possible, note the condition of the container. Check for the following: dents, ruptures, physical damage, valve or bung leaking, and container corrosion.

- Obtain the MSDS for the product.

L.3.2 Secure the Area. In order to secure the area, barriers such as caution tape or cones may be put up. If more than one NWS employee is available, one may perform a security role, keeping other employees out of the area while a second employee notifies a supervisor.

L.3.3 Notify Supervisor(s). When the area is secured so that an unsuspecting individual shall not be harmed by chancing upon the spill, the person who discovered the spill shall notify their Safety or Environmental/Safety Focal Point and the Station Manager.

Important information that needs to be conveyed to the Safety or Environmental/Safety Focal Point and the Station Manager includes:

- exact *location* of the spill,
- *volume* of material released,
- *rate* of release,
- *direction* of spill movement, and
- *product* involved.

Other important information may include:

- color, appearance, and form of spilled substances (for unknowns),
- fires or ignition sources,
- chemical reactions, and
- spill running off the property.

L.3.4 Personal Protective Equipment (PPE). For hazardous materials that can be released into the environment, all potentially affected NWS employees shall have training regarding the proper use of personal protective equipment. For most small spills, the extent of personal protective equipment is limited to chemical resistant gloves, protective eye wear, possibly a respirator (air purifying), and a chemical resistant apron. Steel-toed shoes and other equipment, including non-sparking tools and chemical resistant clothing, may also be required.

L.3.5 Control the Spill. Simply closing a valve on a pipe that is upstream from the release, tightening a bung on a drum, or up-righting a container can easily control many small spills. Employees are not encouraged to take unsafe steps to control spills. For instance, no one shall attempt to upright a 55-gallon drum without assistance or without using a drum cradle.

L.3.6 Contain the Spill. Where “control the spill” refers to stopping the release at the source, “containing the spill” refers to stopping the movement of the spilled material once it has been released. Spill containment may include such things as using dikes, booms, pads, or other materials to stop the flow of the spilled chemical. Spill containment devices are typically specific for the type of chemical. For instance, a boom manufactured for petroleum spills will not be effective in the containment of a caustic material release.

The appropriate spill containment devices shall be placed in the close proximity to the area where these chemicals are stored or used. At NWS facilities, this applies to the emergency generator spill kit, or the mercury spill kit located near a barometer. A spill kit works well for this purpose and may combine the features and equipment necessary to perform spill clean up steps described in Section L.3.

L.3.7 Clean Up. Basically, there are three means of cleaning up a spill. The material may be recovered, absorbed, or neutralized. Once the spill is cleaned up, the debris generated during this operation needs to be disposed of properly. Also, any contaminated equipment (including personal protective equipment) and personnel shall be decontaminated.

- Recovery.

The recovery of a spill requires appropriate equipment, such as a special vacuum unit. Usually, recovery requires some filtering or other means of separating out the debris from the product. For example, there is a special vacuum unit designed to vacuum mercury spills.

- Absorption.

Absorption of a spill requires the use of a material which will not react with the spill but will soak it up, collecting it into a form which may be safely handled.

Pads or booms made of absorbent material are commonly used (this applies to oil spills). Clay-based litters such as a kitty box litter, once commonly used, have been replaced for several reasons. First, the clay-based litters do not absorb many materials. They generate a heavy waste with high disposal cost. Also, they tend to produce dusts, which, in combination with the spilled material, may create a respiratory hazard.

- Neutralization.

If the spilled material is corrosive (either an acid or a base), neutralizing the spill before attempting to containerize the debris may be safest.

Acids may be neutralized with bases such as metallic carbonates (sodium carbonate is known as soda ash) and bicarbonates (sodium bicarbonate is baking soda), or lime (calcium hydroxide).

Bases may be neutralized with acids such as acetic acid (vinegar). For example, potassium hydroxide spills shall be neutralized by a 5 percent vinegar solution.

- Disposal.

Containment debris may meet the Environmental Protection Agency (EPA) regulatory definition of a hazardous waste or hazardous debris [as defined in the Resource Conservation and Recovery Act, (RCRA)]. If so, specific steps shall be taken to ensure the safe disposal of this waste material in accordance with applicable regulatory requirements. Many local jurisdictions have established programs for the collection of hazardous waste from small businesses, small Government facilities, households, etc. Municipal landfill or hazardous material transfer stations shall be contacted to verify if they can accept hazardous waste generated at small Government facilities.

If the debris does not meet the regulatory definition of a hazardous waste, it may be disposed of along with commercial rubbish. If there are any questions regarding the disposal of hazardous waste, the National Oceanic and Atmospheric Administration (NOAA) Regional Environmental Compliance Officer (RECO) or the State Department of Environment or the state public health officer shall be contacted by RECO. Local

landfill may also be able to help with determining the best way to dispose the waste (note: accepting liquid waste is illegal for landfills).

- Decontamination.

Equipment and personnel decontamination is typically very easy. The following is a simplified overview of decontamination procedures. The actual steps taken shall be appropriate for the chemical being handled during the spill cleanup. MSDS give specific recommendations on decontamination.

- a. PPE (e.g., gloves) utilized during cleanup can be thrown away (preferably with the contaminated debris). The gloves shall be inverted so that the contamination is “contained” inside the glove.
- b. Respirators shall be washed with a mild soap and water, thoroughly dried, and inspected prior to storage (cartridges shall be removed in most instances). Alcohol shall not be used to clean respirators because it can degrade the face piece material. Respirators shall be stored in a clean, dry bag away from sources of heat, chemicals, light, and dust.
- c. Tools may also be washed in a mild soap-and-water solution (trisodium phosphate is a very common cleaner used to decontaminate equipment).
- d. If NWS personnel come into contact with chemical (skin, eyes, etc.), the affected area shall be washed, generally by using plenty of water and a mild soap (for skin). MSDS recommendations shall be followed.
- e. NWS personnel involved in a spill cleanup shall be especially careful of material which may be on the soles of their shoes. The “decontamination” area shall be near the spill site to avoid tracking contamination into clean areas. Certain materials, such as leather, are difficult to decontaminate adequately.

- Reporting.

Section 304 of the Superfund Amendments and Reauthorization Act (SARA) and the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) require generators of waste to report a release of hazardous substance equal to or greater than reportable quantities. The release shall be reported only to the National Response Center (1-800-424-8802) and the State Emergency Response Commission. Regional Environmental/Safety Coordinator and RECO must be immediately notified when the spill occurs. This is applicable to 1 pound of mercury, 100 pounds of spent solvent (tetrachlorethylene), 1 pound of polychlorinated biphenyls (PCB), and other regulated substances.

- Waste Transportation

If the field office and Operating Unit does not generate more than 100 kg (220 lbs.) of hazardous waste or 1 kg of acute waste, it is defined as a Conditionally Exempt Small Quantity Generator (CESQG). The CESQG facility is excluded from full EPA requirements applicable to hazardous waste transportation, labeling, and manifesting. However, DOT regulations apply when waste is transported to the disposal facility.

The CESQG status is applicable to each NWS office, except the National Reconditioning Center (NRC) and the National Data Buoy Center (NDBC). CESQG status may not apply to some NWS leased facilities (e.g., at universities, FAA offices, etc.). If NWS offices have CESQG status, NWS employees can self-transport small quantities of hazardous waste. Otherwise, certified waste transporters shall be used.

*Hazardous materials or waste can be transported **only in the Government vehicles.***

When self-transporting the waste to a disposal/collection site, NWS personnel shall be aware that rules imposed by the Department of Transportation (DOT) and by the Environmental Protection Agency (EPA) shall be followed.

L.4 Mercury Cleanup. Mercury is a naturally occurring metal found throughout the environment as the normal breakdown of minerals in the earth's crust. Mercury is a heavy metal that, in a liquid state, can readily evaporate even at room temperature. An increase in room temperature would raise the rate of mercury evaporation. Vapors are colorless and odorless, therefore, they cannot be detected by human senses. Only mercury detectors (sniffers) can detect actual levels of mercury vapors in the surrounding air. Most exposures on the job occur as a result of inhaling mercury vapor or by getting mercury on the skin when cleaning up a spill of metallic mercury. The Occupational Safety and Health Administration (OSHA) regulates the level of mercury vapors to which workers can be exposed. That level is called the Permissible Exposure Limit (PEL) and it is 0.1 mg of mercury in one cubic meter of air. Several studies conducted at the National Institute of Safety and Health (NIOSH) showed that a short exposure to a higher level of mercury vapors is less dangerous than a prolonged exposure to a lower level of mercury vapors. NIOSH recommends a PEL of 0.05 mg of mercury in one cubic meter of air.

NWS employees can encounter mercury spills from broken thermometers, switches, old radars' rotary joints, Fortin barometers, and standard barometers.

L.4.1 Small Mercury Spills from Broken Thermometers/Mercury Switches. It is easier to clean up small mercury spills from broken thermometers and mercury switches, than larger spills from broken barometers. The level of mercury vapors from small spills will most likely not exceed the PEL, unless the spill occurs in an extremely small space without any ventilation. However, to be on the safe side, when a spill occurs, one shall lower the space temperature and ventilate the space if possible. Opening windows and using portable exhaust fans to improve ventilation is advisable.

It is required that each field office, Operating Unit, and headquarters office have a "mercury spill kit," which includes a small manual vacuum pump, a jar of mercury absorption powder, and proper eye and hands protective equipment. A kit can be purchased from Lab Safety Supply (1-800-356-0783) for approximately \$155. Usage instructions are attached to the kit. The procedures for cleaning up mercury spills are as follows:

- Read the MSDS before beginning the clean up procedure.
- Wear polyethylene, rubber, or polyvinyl chloride (PVC) gloves, plastic disposal boot protectors, and safety glasses when performing a cleanup.
- Use the manual vacuum pump to vacuum a mercury puddle and droplets of mercury.

- If spill occurred on a hard surface and the removal of small droplets by vacuum pump is almost impossible, use mercury absorbent sponges to finish the clean up.
- In deep cracks mercury absorbent powder shall be wiped over the contaminated areas to ensure that all residual mercury droplets will be converted into a mercury amalgam. The amalgam then can be collected and removed.
- The removal of mercury from carpeted areas is very difficult. All visible droplets of mercury shall be picked up by a mercury vacuum pump. After that, a carpet shall be treated with a paste of mercury absorbent powder and water. The level of mercury vapors shall be checked as described in the clean up procedure for barometer spills in succeeding paragraphs.
- Mercury recovered from a spill can be stored in plastic or glass bottles. All mercury residues shall be collected into a plastic zip-lock bag. Usage of plastic bags is not sufficient if broken glass is involved.
- Sponges designed to absorb small mercury spills on hard surfaces can be used. They can be bought separately, for \$16, from Lab Safety Supply. A sponge needs to be moistened and small droplets can be simply wiped up. The sponge and its container shall be properly disposed of as described below.
- If field office and Operating Unit has an arrangement with a local hazardous waste disposal company and the company handles mercury, arrange for pick up. Otherwise, find other local companies that can provide mercury pickup and disposal. Also, check with local recycling facilities if they accept small quantity of mercury.
- Arrange with your local Hazardous Material Transfer Station (usually associated with a landfill station) for mercury disposal. Many counties have program in place to accept wastes from small businesses and small federal facilities. The Hazardous Material Division at a Transfer Station usually requires advance notice for hazardous material acceptance. They will accept pure mercury as well as broken thermometers and mercury switches. To prevent any spill accidents and mishandling of waste, use proper containers and keep the appropriate MSDS on hand while transporting mercury waste.
- Always place the mercury container in a secondary container (a metal or plastic drum with a lid) to prevent any leaks or spills in case of an accident. Affix the proper label to the container: WASTE MERCURY, UN 2809, RQ. EPA hazardous waste identification number for mercury is U151.
- When self-transporting the waste, allowed only for CESQG, the rules of DOT Title 49 of the Code of Federal Regulations, Parts 100-199 (49 CFR 100-199) shall be followed. The personnel involved in transporting hazardous waste shall receive required DOT training. Otherwise, a local certified waste transporter shall be used.

L.4.2 Large Mercury Spills from Broken Barometers. The barometers used by personnel at NWS facilities contain a large amount of mercury. The Fortin barometer contains approximately 1.6 pounds of mercury, and the standard barometer can hold up to 4-5 pounds of mercury. These amounts of mercury, if spilled over the large floor area, can evaporate rapidly even at the room temperature. Since mercury vapors present a serious health hazard, immediate spill response actions are required. Facilities that have mercury barometers shall make arrangements for

emergency cleanup with the local Fire Department or local spill cleanup company. A person in charge of the spill response (e.g., Safety and Environmental/Safety Focal Point or other NWS personnel) shall attempt to contain the spill and to reduce mercury evaporation. Once the spill is contained, the Regional Environmental/Safety Coordinator, RECO, and NWS Safety Officer shall be notified.

The following steps shall be followed in case of a large mercury spill:

- Do not disturb a mercury puddle (any mercury movement will increase evaporation). Evacuate personnel if the spill is extensive, the room is small and the ventilation is poor. Isolate the spill area with signs, barriers, or tapes.
- Decrease room temperature, if possible.
- Prevent mercury vapors from entering the heating, ventilation, and air conditioning (HVAC) system by blocking return air registers.
- Ventilate area as much as possible (e.g., open windows). Use portable exhaust fans to increase air movement and to disperse the mercury vapors.
- The levels of mercury vapors in the air shall be monitored as soon as possible. A mercury sniffer is only device that can detect mercury concentration in the air surrounding the spill area. The local safety equipment rental stores shall be called to check if they have a mercury monitor available immediately. If measured mercury concentration is below 0.05 mg/m^3 , the spill is contained, and the area is ventilated adequately, personnel can remain in the office. If mercury reading exceeds 0.05 mg/m^3 , all employees shall immediately evacuate the office.
- If you are unable to monitor the air and, therefore, assure employees safety, call a local hazardous spill cleanup company to provide emergency cleanup or local Fire Department if prior arrangements have been made. Each field office and Operating Unit shall have a list of such companies on hand. Services of the companies that can provide cleanup of barometer spill shall be used at all NWS facilities.

All NWS employees working with mercury-containing equipment need to understand that mercury presents a serious danger to their health and safety. Therefore, the mercury-containing equipment, especially barometers, shall be handled with extreme care. In the event of a spill, the primary goal is to protect the employees from exposure to mercury vapors.

Mercury spills shall be properly reported. For example, if one pound of mercury is released into the environment (this does not apply if spill occurred within enclosed building or enclosed containment structure where there is no release to air, water, or soil), it shall be reported within 24 hours to the National Response Center (tel. 1-800-424-8802), and/or state or local environmental agencies. A respective RECO shall be contacted to report a spill.

L.5 Printer Plotter Module Toner Disposal.

L.5.1 Utilization of Safety Kleen or Other Hazardous Waste Disposal Company. Arrange for a semi annual pick up of used toner. This is a more expensive option, however, it decreases NWS liabilities. Regional headquarters have a list of Safety Kleen offices in the vicinity of each WFO or WFO/RFC. Used toner shall be stored in small double walled containers with the lid closed and properly labeled as “WASTE TONER.” The date when the container was first used shall be

posted. As AFOS equipment from the spin-down WFOs is decommissioned, the amount of toner/dispersant disposal effort is expected to decline.

L.5.2 Local Collection Facility. A local hazardous material transfer station may accept waste toner. If NWS facility has CESQG status, waste toner can be self-transported to such facility. According to DOT standards, the toner is classified as a combustible liquid, packing group III. Containers for transporting toner shall be no more than 1 gallon, and can be made of plastics, glass, earthenware or metal when shipped by commercial shipping companies (Federal Express, UPS, etc.). The reuse of the original containers is encouraged; otherwise, small waste drums can be used for self-transporting to the local collection facility (e.g., hazardous material transfer station). It is recommended that the container be placed in an additional outer container filled with absorbing materials. The container shall be marked:

Waste combustible liquid n.o.s.

(Isoparaphinic hydrocarbon mixture)

NA 1993

No other container labels or car placards are required when using ground transportation. Note that if the waste is transported by highway, placards are not required for vehicles carrying less than 1,000 lbs. of hazardous waste (up to two 55-gallon drums, depending upon specific weight of the substance, 8-10 lb./gallon). However, MSDS shall be placed near the container.

L.5.3 Empty Toner Container. A bottle or other container is classified as “empty” when all waste has been removed using common practices such as pouring, pumping, aspirating, etc. Bottles of toner are “legally” empty, and, therefore, not regulated when all contents have been transferred. Since original toner containers are relatively small, all toner can be removed by pouring. There shall be no visible residue on the bottom of the container. Such container is considered to be empty and, therefore, not regulated, and can be disposed into regular trash. Note that a container with residue (as is often the case with AFOS toner) is not legally “empty” and shall be disposed as a hazardous debris.

L.6 Cleanup Towels. The EPA classifies any cleanup towels as hazardous when they display “hazardous characteristics.” Towels contaminated with toner, diesel fuel, and solvents display ignitable characteristics. The following is the EPA definition of ignitability:

Non-liquids “capable, under standard temperature and pressure, of causing fire through friction, absorption of moisture or spontaneous chemical changes and, when ignited, burn so vigorously and persistently that it creates a hazard.”

Cleanup towels soaked with the hazardous substances would meet the definition and are identified as a hazardous waste. In some states, towels contaminated with mineral oils are classified as hazardous waste. Also, some states allow the cleanup towels to be washed by industrial cleaning facility and then re-used. In any case, call the state environmental agency to determine current regulatory requirements applicable to cleanup towels. Since regulations vary so much, the best management practice would be to collect and store towels at the site and dispose of them properly. Disposal options include a municipal hazardous material transfer/collection site or a licensed disposal company. Cleanup towels contaminated with flammable or other hazardous substances shall be stored and transported in fire-safe containers. The containers shall be made from compatible materials and marked "contaminated towels." Local fire departments may require specific types of containers, colors, and labels. Contaminated towels shall not be accumulated on-site for more than 180 days.

L.7 Batteries.

The paragraphs below describe general requirements applicable to batteries. NWS personnel shall always consult with the state agency regarding current status of the rules for batteries.

L.7.1 Automotive lead acid batteries. These batteries are special hazardous waste regulated by EPA and shall be taken by NWS personnel to local collection sites or retailers for recycling.

L.7.2 Mercury-Containing and Rechargeable Batteries. Mercury-containing and Rechargeable Battery Act was passed by Congress and signed by the President in 1997.

This Act:

- Requires batteries to be labeled: "Battery shall be recycled or disposed of properly".
- Prohibits the sale of alkaline, magnesium, and carbon-zinc batteries that contain mercury and mercury oxide batteries.
- Prohibits the sale of nickel-cadmium and sealed lead-acid batteries if they are not labeled properly.

Recyclable Battery Recycling Corporation (RBRC) has been created to establish a national battery recycling program. The RBRC information service is available at 1-800-8-Battery.

L.7.3 Other Batteries. As there are so many different types of batteries used at NWS offices, it would be costly and time-consuming to conduct a laboratory test of each battery. Such tests would determine if a particular type of battery is "hazardous" (e.g., lead acid batteries). EPA does not provide data regarding which batteries are "hazardous waste batteries." It is a good operating practice to classify all batteries as "hazardous," and dispose of them at a collection site or a recycling facility.

L.7.4 General Precautions. Batteries shall be handled in such a manner that a release of the battery's contents to the environment is prevented. Under no circumstances shall batteries be disposed of in the trash.

- Keep batteries in a closed container compatible with the content of the batteries. The container shall not show leaks, spills and damage that could cause future spills. A specialized plastic container can be purchased from commercial distributors such as:

Lab Safety Supply

P.O. Box 1368

Janesville, Wisconsin 53547-1368

Telephone: 1-800-356-0783

<http://www.labsafety.com>

New Pig

One Pork Avenue

Tipton, Pennsylvania 16684-0304

Telephone: 1-800-621-7447

- Do not break up batteries or open the closed cells.
- Different batteries can be placed in the same container; however, some collection sites require batteries to be separated by type.
- Clearly mark the container: "Used battery(ies)."

L.7.5 Transporting Batteries. Arrange with a local waste disposal company to pick up the batteries for disposal/recycling. This is a preferable method of disposal. When picking up batteries by an outside contractor is not feasible, either of the two methods described below is recommended:

- Check if local department or retail specialty stores accept used batteries for recycling and obtain any specific conditions for battery acceptance. As an infrastructure for universal waste collection develops, there will be more collection sites available. When NWS employees self-transport batteries to a collection site, they become universal waste transporters. The corresponding MSDSs shall be kept in the vehicle during transport. Small transported quantities are excluded from full regulatory requirements (e.g., vehicle placarding, shipping papers) *only when Government vehicles are used*.
- Deliver used batteries to a municipal transfer station/collection facility which may be associated with a municipal landfill.

L.8 Shipping Instructions for Decommissioned Equipment.

L.8.1 Transport of Unbroken Thermometers and Mercury Switches. The Instrument Decommissioning Plan prepared at WSH, by Engineering Division personnel, includes a requirement to return unbroken thermometers, mercury switches, and mercury batteries from equipment replaced by ASOS to NRC.

Shipping materials can be ordered from NLSC by contacting the shipping department at 1-816-926-3990. Please be prepared to provide the following information when ordering shipping materials from NLSC:

- Organizational Code
- Address of ordering unit
- Amount of items to be shipped
- ASN
- Accounting Code
- Any Special Instructions

L.8.2 Shipping Mercury Barometers. Mercury spills resulting from the breakage of barometers must be prevented by following proper shipment procedures. The procedures for preparing the barometer for shipment using Princo packing material are described below. Special packing material for the G010D barometer shall be ordered from NLSC. Packing material included all required labels and markings.

- Before removing the barometer to be shipped from its mountings, adjust the mercury column all the way up to prevent breakage or loss of vacuum during shipment. This can be done by a series of three or four turns of the cistern screw. Pause for about thirty (30) seconds between each series of turns to assure that the air has time to bleed out of the cistern. When the mercury column gets to the top of the glass tube, you will feel a marked resistance to any further turning of the cistern screw. At that point, wait about five minutes and try the cistern screw again to make sure the column is all the way up. The barometer can now be packed for shipment.
- With the barometer hanging only by the top hanger, slide the plastic bag up over it.
- Remove the barometer from the hanger.
- Remove excess air from the bag and place a tie wrap around the top of the plastic bag to seal it.
- Place the bagged barometer into a foam, rubber-lined inner carton.
- Insert the inner carton containing the bagged barometer into the cardboard sleeve by turning it upside down and sliding it into the sleeve.
- Mark “Cistern End” of the sleeved barometer.
- Place a foam end cap over each end of the sleeve and insert the sleeve into the outer carton.
- Wrap wide filament tape around the outer carton at the center and near each end.
- Mark “Cistern End” of the outer carton, and label the outer carton with “LAY FLAT” and “FRAGILE” stickers or write it with a large red felt pen.
- The barometer can now be safely shipped.
- Fill out the Shippers’ Declaration of Dangerous Goods form:

NOTE: Ask NLSC to prepare Government Bill of Lading
--

Proper Name:

Mercury Contained in Manufactured Articles

NWSM 50-1115 SEPTEMBER 15, 2009

Class or Division:	8
UN No. :	UN 2809
Quantity and Type of Packing:	Cardboard Crate Containing 698.5 g (1.54 lb) Mercury Inside Sealed Plastic Liners
Packing Instruction:	805

ADDENDUM II

Hazard Communication WFO Springfield, MO

January 20, 2000

**Section C- NATIONAL WEATHER SERVICE
HAZARD COMMUNICATION PROGRAM**

The following written Hazard Communication Program has been established for:

National Weather Service Office: <u>Springfield, MO</u> Central Region National Weather Service National Oceanic and Atmospheric Administration U.S. Department of Commerce

It is prepared to comply with the U.S. Department of Labor, Occupational Safety and Health and Administration Standard Title 29 Code of Federal Regulations (CFR) Part 1910 Section 1200, Hazard Communication standard requirements.

The Station Manager (Meteorologist In Charge (MIC) at this site:

<u>William Davis</u> (Meteorologist In Charge) name
--

is responsible for the occupational safety and health of the personnel and the Hazard Communication program at the site. Functional responsibility for the Hazard Communication Program has been delegated to:

<u>Larry Dooley</u> (Safety or Environmental/Safety Focal Point) name
--

The Safety or Environmental/Safety Focal Point shall review and update the program on a semiannual basis. This program applies to all worksites associated with (circle one):

- a. Weather Forecast Office (WFO)
- b. Weather Forecast Office/River Forecast Center (WFO/RFC)

NWS employees, their designated representatives, and contractors at this site, and upon request, the Occupational Safety and Health Administration (OSHA) representatives, emergency and medical service providers have access to this written Hazard Communication Program at the following location:

Hazardous Materials Reference Binder and Station Duty Manual in the Operations Room Reference Library

The worksites listed on this page are sites where NWS personnel may be exposed to the chemical hazards under normal working conditions or during an emergency situation.

Locations Associated with the WFO or WFO/RFC			
Site Location:	Springfield	State:	Missouri
List of the offices, WSR-88D Radar Data Acquisition Subsystems (RDAs), Upper Air Inflation Buildings (UAIBs), Automated Surface Observing System (ASOS) sites, National Oceanic and Atmospheric Administration (NOAA) Weather Radio, cooperative stations, transition power maintenance shelters, storage sites, etc., associated with this Weather Forecast Office (WFO) or WFO/River Forecast Center (RFC).			
Type of Facility/Description		Location	
National Weather Service Office		5805 W. Hwy. EE, Springfield, MO 65802-5400	
Upper Air Inflation Building		same	
WSR-88D (RDA bldg. and Radar dome)		same	
NWS storage bldg.		same	
KSGF ASOS		Springfield-Branson Regional Airport	
KJLN ASOS		Joplin Regional Airport, Joplin, MO	
KVIH ASOS		Rolla/Vichy Airport, MO	
KUNO ASOS		West Plains, Airport, Pomona, MO	
Wind profiler		near Conway, MO	
NWR WXJ-46 (SGF)		Fordland, MO (KY-3 TV tower)	
NWR WXJ-61 (JLN)		Avilla, MO (KAMO tower)	

Locations Associated with the WFO or WFO/RFC			
Site Location:	Springfield	State:	Missouri
List of the offices, WSR-88D Radar Data Acquisition Subsystems (RDAs), Upper Air Inflation Buildings (UAIbS), Automated Surface Observing System (ASOS) sites, National Oceanic and Atmospheric Administration (NOAA) Weather Radio, cooperative stations, transition power maintenance shelters, storage sites, etc., associated with this Weather Forecast Office (WFO) or WFO/River Forecast Center (RFC).			
Type of Facility/Description		Location	
NWR WXM-81 (HER)		Lake Pomme-de-Terre Dam (COE tower)	
NWR WXJ-90 (AIZ)		Osage Beach, MO (Sky Tech Comm. tower)	
NWR WWF-76 (SUM)		Summersville, MO (Howell-Oregon Elec. Co-op tower)	
Resistance "E" gage		Galena, MO	
Limited Automatic Remote Collection (LARC)		River gage	
		1. Eminence, MO (co-located near Co-op)	
		2. Jerome, MO (co-located near Co-op)	
		3. Fulton, KS	
Limited Automatic Remote Collection (LARC)		Rain gage (belongs to COE)	
		4. Garrison, MO	
		5. Isabella, MO (co-located near Co-op)	
		6. Dora, MO (co-located near Co-op)	
		7. Vanzant, MO	
		8. Wassola, MO (co-located near Co-op)	
		9. Willow Springs, MO	
Cooperative Observing Sites		with Fisher-Porter rain gages:	
		1. Columbus, KS	

Locations Associated with the WFO or WFO/RFC			
Site Location:	Springfield	State:	Missouri
<p>List of the offices, WSR-88D Radar Data Acquisition Subsystems (RDAs), Upper Air Inflation Buildings (UAIBs), Automated Surface Observing System (ASOS) sites, National Oceanic and Atmospheric Administration (NOAA) Weather Radio, cooperative stations, transition power maintenance shelters, storage sites, etc., associated with this Weather Forecast Office (WFO) or WFO/River Forecast Center (RFC).</p>			
Type of Facility/Description		Location	
		2. Uniontown, KS	
		3. Alley Spring, MO (at Ranger station)	
		4. Appleton City, MO	
		5. Bolivar, MO	
		6. Cassvile, MO (at Ranger station)	
		7. Dora, MO (co-located near Co-op)	
		8. Lakeside, MO	
		Lebanon, MO	
		Licking, MO	
		Lockwood, MO	
		Marshfield, MO	
		Miller, MO	
		Mountain Grove, MO	
		Nevada, MO (at Water Plant)	
		Osceola, MO	
		Ozard Beach, MO	
		Lake Pomme-de-Terre Dam	
		Rolla, MO (at University of MO Rolla)	
		Salem, MO	

Locations Associated with the WFO or WFO/RFC			
Site Location:	Springfield	State:	Missouri
List of the offices, WSR-88D Radar Data Acquisition Subsystems (RDAs), Upper Air Inflation Buildings (UAIBs), Automated Surface Observing System (ASOS) sites, National Oceanic and Atmospheric Administration (NOAA) Weather Radio, cooperative stations, transition power maintenance shelters, storage sites, etc., associated with this Weather Forecast Office (WFO) or WFO/River Forecast Center (RFC).			
Type of Facility/Description		Location	
		Senaca, MO	
		Spring City, MO	
		Stockton Lake Dam	
		Table Rock Lake Dam	
		Truman Lake & Reservoir Dam	
		Vienna, MO	
		West Plains, MO	

C.1. Hazardous Chemical List. The Station Manager has the primary responsibility to ensure that a list of hazardous chemicals used at the WFO or WFO/RFC and associated sites is prepared and kept current. The Safety or Environmental/Safety Focal Point,

Larry Dooley, is delegated the responsibility and authority to establish and update the Safety or Environmental/Safety Focal Point)

master hazardous chemical list semiannually. A new item shall be added on the master chemical list after the Safety and Environmental/Safety Focal Point has reviewed the material safety data sheet (MSDS) and cleared it for purchase (see paragraph C.3 for purchasing requirements). Only the Safety or Environmental/Safety Focal Point or the station manager’s designated representative can update the master hazardous chemical list. Personnel in charge of associated sites are responsible for updating the site hazardous chemical list in accordance with the master list.

Section D of the NWS Hazard Communication Program Kit contains a master list of all known chemical products and items containing chemicals to which employees at this site are or may be potentially exposed (e.g., via spills). Separate lists are available for RDAs, UAIBs, ASOS, NOAA Weather Radio, cooperative stations, etc. and are posted and accessible to fire department personnel during emergency situations. Local municipal fire officials may request specific arrangements for displaying the lists outside the building(s).

The Worksite Hazardous Chemical List includes the following:

- a. product/generic name, as shown on the label and MSDS (names shall be identical);
- b. manufacturer's or distributor's address, and, if available, telephone number;
- c. generic name;
- d. operational area used;
- e. quantity on hand;
- f. date entered into the system;
- g. NSN/ASN, if applicable; and
- h. location where used or stored.

C.2. Material Safety Data Sheets. MSDS provide specific information on the chemical product. OSHA requirements for MSDS and its format are described in Section E. The MSDS for all chemicals to which employees may be exposed at this site are maintained in (*circle one*):

- a. Section E
- b. Under separate cover.

The Safety or Environmental/Safety Focal Point is responsible for compiling and maintaining a complete master set of MSDSs for chemical products identified on the hazardous chemical listing (see Section D). The MSDS shall be a fully completed OSHA form 174 (See Section I) or an equivalent.

For products already in use at NWS facilities for which there are no current MSDS, the Safety and Environmental/Safety Focal Point shall ensure that a corresponding MSDS is obtained from the manufacturer or vendor.

If a product is ordered through the Consolidated Logistics System (CLS), the shipment shall automatically include MSDS(s). If the MSDS is not included with a shipment, the ordering employee shall contact the National Logistics Support Center (NLSC) and request the corresponding MSDS. All purchase requisitions for new chemical products shall be reviewed and cleared by the Safety or Environmental/Safety Focal Point, as described in paragraph 3. The MSDS shall be submitted to the Safety or Environmental/Safety Focal Point, who shall assure that it contains all information required by the standard. An MSDS checklist is included in Section J.

The Safety or Environmental/Safety Focal Point shall contact a manufacturer or vendor if within a reasonable time, an MSDS has not been received, or additional clarification and research is necessary. It is advisable to contact the manufacturer's MSDS Technical Service Department first by telephone. When this approach is not successful, the Safety or Environmental/Safety Focal Point shall contact the manufacturer by letter (see Section I for sample letters requesting MSDS or additional information). A copy of the letter shall be retained to document efforts to obtain the MSDS.

The Safety or Environmental/Safety Focal Point shall ensure that an MSDS containing trade secret chemical components include the manufacturer's emergency number. The manufacturer shall disclose the identity of a trade secret component in case of medical emergency to a treating physician. If the product with a trade secret component requires monitoring or other special protective measures, industrial hygiene professionals have a right to require the identity of trade secret components. The Safety or Environmental/Safety Focal Point shall contact the DOC Regional Safety and Health Manager (RSM) at the pertinent Administrative Support Center (ASC), or the NWS Regional Environmental/Safety Coordinator for technical advice in such cases.

C.2.1 MSDS Sets to Maintain. A master MSDS set shall be maintained at the WFO or WFO/RFC as part of the Hazard Communication Program. In addition, uniquely defined MSDS subsets shall be established and maintained by the Safety or Environmental/Safety Focal Point for the:

- RDA,
- UAIB and/or balloon inflation launching shelter (BILS),
- ASOS
- NOAA Weather Radio
- cooperative stations
- transition power maintenance shelter (TPMS),
- storage sites, and
- other sites associated with the facility.

In addition, supervisors shall ensure that applicable MSDS are available within individual work areas under their control.

Copies of MSDS can be obtained from the Safety or Environmental/Safety Focal Point.

C.3 Purchasing Requirements. Purchase orders for products that are hazardous or may contain hazardous chemicals/materials shall include a provision, or be accompanied by a written request, to the vendor or supplier that:

- a. an up-to-date MSDS is provided,
- b. containers bear required identification and warning labels (see paragraph C.4 for labeling requirements), and
- c. Department of Transportation (DOT) requirements for shipment are met.

Prior to the acquisition of new chemical products, the MSDS for those products shall be obtained and forwarded to the Safety or Environmental/Safety Focal Point for review in order to determine if the potential for physical and health hazards exists, and if there are any special requirements for shipment, disposal, and storage. If working with the product would present more than a minor health hazard and require special preventive measures (local exhaust, air monitoring), the usage of such a product shall be discouraged. The product shall be replaced by less hazardous alternatives, if available. NWS employees are mandated to actively search for viable replacement of hazardous products with environmentally 'friendly' products that are less

hazardous to human health and the environment. Product cost estimates shall include all expenditures for operating and disposing of that product. This includes the costs for the initial purchase of the product as well as the use of personal protective equipment and the proper disposal of a used product or residue.

While MSDS are not required to be physically attached to a shipment, they shall accompany or precede the shipment. When the manufacturer/supplier fails to send an MSDS with a shipment, the Safety or Environmental/Safety Focal Point shall obtain one from the manufacturer/supplier.

When purchasing hazardous materials from the foreign companies, NWS personnel shall ensure the following:

- a. Import of hazardous material(s) into the U.S. is not prohibited by any U.S. agency and/or regulations.
- b. Shipment of hazardous material(s) into U.S. is performed in accordance with applicable U.S. DOT regulations.

C.4. Container Labeling and the Use of Placards. Chemical manufacturers, importers, and distributors are mandated by law to label, tag, or mark all containers leaving their plants or warehouses. Unlike the MSDS, the label is not an exhaustive description of the chemical substance. Rather, the label is meant to warn users of health and/or chemical hazards. At a minimum, labels shall list:

- a. name of the chemical, and common names, if any;
- b. signal word for hazard; CAUTION, DANGER, WARNING, etc., and hazard statement (see Section F for examples); and
- c. the name and address of the manufacturer, importer, distributor, or responsible party.

In most cases, chemical products purchased in retail stores have the required labeling. Products purchased in bulk from wholesale distributors or supply houses are more likely to have labeling problems and, therefore, shall be thoroughly checked.

Personnel who purchase or receive shipments shall verify that each container's label contain all the information specified in subparagraphs a, b, and c. The following additional requirements shall be met:

- a. the chemical name shall be identical with the one listed on the MSDS. For items ordered through CLS, there shall be a national stock number (NSN) and agency stock number (ASN) on the label;
- b. labels shall be legible and in English;
- c. labels shall not be defaced or otherwise damaged; and
- d. container labeling shall be in conformance with hazardous material transportation regulations promulgated by Department of Transportation (DOT) and set forth in Title 49 CFR. DOT requires proper shipping name, UN ID #, and hazard labels on shipping container.

If any problems are discovered, shipments shall not be accepted, and the Safety or Environmental/Safety Focal Point shall be notified. If the problem can not be resolved locally, the NWS Regional Environmental/Safety Coordinator, the RECO, or DOC RSM at ASC shall be contacted for advice regarding further action.

Station managers and supervisors are responsible for ensuring that personnel use only labeled/marked containers. To comply with this requirement, existing unlabeled containers shall be labeled (if the content is known) and any new purchase or shipment shall be checked before the product is used.

To further ensure that employees are aware of the chemical hazards of materials used in their work areas, supervisors for each work area and/or shift shall ensure that all secondary containers are labeled. Any container label that becomes damaged shall be replaced. This label may be replaced with either an extra copy of the original manufacturer's label, with generic labels [National Fire Protection Agency (NFPA), Department of Defense (DoD)] or any hand printed in indelible ink that correctly states all data required by subparagraphs a, b, and c (see G for samples). For help with labeling, supervisors shall call the Safety and Environmental/Safety Focal Point at the Central Office. When transferring chemicals from one container to another (e.g., transfer of a solvent from a 5 gallon container into a 1 gallon can), the person responsible for the transfer is also responsible for the proper labeling of the new container.

Labels may not be required on temporary **portable containers** in which chemicals are:

- a. transferred from labeled containers,
- b. when such a container is intended for the transferring employee's immediate use,
- c. the quantity does not exceed a one day supply, and
- d. the container is used only when an employee is present.

If all of these conditions are not satisfied, the container shall be labeled. Care shall be taken by an employee and supervisor to assure that chemicals are not disposed into temporary containers that previously held incompatible chemicals, unless the containers are properly cleaned.

Note: *No flammable material may be placed into temporary containers not designated for flammables.*

Placards or signs which convey the hazard information may be posted in lieu of container labels for stationary containers within a work area which have similar content and hazards, e.g., hydrogen for generators and hydrogen storage area.

The Safety or Environmental/Safety Focal Point shall inspect container labeling at least semiannually in conjunction with the hazardous list and MSDS update. Any unlabeled containers of an unknown content and surplus chemical products shall be disposed of by a certified disposal company. There are a number of Federal and state regulations that govern the handling, transport, storage, and disposal of hazardous chemicals. Any surplus activity shall be planned ahead including accumulation, storage, and disposal of surplus chemicals. Surplus activities shall be coordinated with RECO and the NWS Regional Environmental/Safety Coordinator.

Pesticides, foods, food additives, colorings, drugs, and consumer products that are controlled by other federal agencies and laws do not require labeling under the OSHA Hazard Communication Standard.

C.5. Employee Training and Information. NWS personnel who (even occasionally) work with, purchase, or are potentially exposed to chemicals shall receive initial training on the Hazard Communication Program. The Safety or Environmental/Safety Focal Point shall initially receive comprehensive classroom type environmental and safety training that includes training on the requirements of the Hazard Communication Standard.

The Station Manager, along with the Safety or Environmental/Safety Focal Point shall determine which WFO or WFO/RFC personnel have not yet received Hazard Communication training and need to be trained locally. A recommended source of training is the audio/video Federal Hazard Communication Program, specifically developed for the Federal Government personnel. More information can be found in Section K, Training Program and Appendix IV, References. The Safety or Environmental/Safety Focal Point shall assume an active role in personnel training. The training program shall include the following topics:

- a. an overview of the requirements contained in OSHA standard 29 CFR 1910.1200;
- b. chemical and physical properties (flashpoint, reactivity, etc.) of hazardous materials and associated physical hazards (explosive, flammable, etc.);
- c. health hazards, including signs and symptoms of exposure and routes of entry;
- d. how to interpret labels and MSDS;
- e. methods and observation techniques used to determine the presence or release of hazardous chemicals in the work area (such as monitoring, visual appearance, or odor, etc.);
- f. how to lessen or prevent exposure to the hazardous chemicals through usage of safe work practices, engineering controls (ventilation), and personal protective equipment;
- g. chemicals present in the work area;
- h. location and availability of the written Hazard Communication Program, hazardous chemical lists, and MSDSs; and
- i. emergency procedures to follow if an employee is exposed to these chemicals.

Each new employee that has not been trained shall receive the initial training. Upon completion of the initial training, each employee shall sign the training form (see Section G) or a form approved by the Station Manager.

When new chemicals or chemical products are introduced into the work area, the Safety and Environmental/Safety Focal Point shall:

- review the MSDS associated with the chemical products,
- identify potential hazards and determine hazard control requirements, if applicable, and
- ensure that all employees working with or exposed to the hazardous chemicals are properly trained in their use.

Training of NWS personnel shall be done whenever a new hazard is introduced into a workplace. Refresher training shall take place based upon an evaluation by the Station Manager along with the Focal Point. The need for refresher training shall be based on employee demonstration that he/she has a thorough understanding of the Hazard Communication Program or based on personnel turnover.

C.6. Hazardous Non-Routine Tasks. Infrequently, NWS employees are required to perform hazardous non-routine tasks. Prior to starting work on such projects, affected employees shall be given information by their supervisor and the Safety or Environmental/Safety Focal Point about the hazards to which they may be exposed during such activity. If more technical advice is required, call the NWS Regional Environmental/Safety Coordinator, RECO, or RSM at ASC.

The information shall include:

- MSDS and description of other physical and health hazards,
- personal protective equipment and safety measures the employee shall use,
- measures that the Station Manager or his designee has taken to lessen the hazards associated with non-routine task, including area ventilation, assignment of a second person or safety observer, spill emergency procedures, etc.

C.7. Chemicals in Unlabeled Pipes. Work activities are often performed by employees in areas where chemicals are transferred through unlabeled pipes. Pipes are not required to be labeled; however, employees shall be informed of their content. The WFO or WFO/RFC may have the following unlabeled pipes: potable water, sewer, oil piping, air conditioning, equipment piping (e.g., air conditioning piping contains Freon that is asphyxiant; maintenance on such piping shall be done only by certified mechanics with specialized recovery equipment).

Prior to starting work in these areas, employees shall contact the responsible supervisor for information regarding:

- the chemical(s) in the pipes,
- potential health hazards, and
- safety precautions which shall be taken.

C.8. Station Manager Responsibilities. The Station Manager, with assistance of the site Safety or Environmental/Safety Focal Point, shall ensure that each employee has a basic knowledge of the information contained in MSDS and an understanding of proper use of that information. The Station Manager shall ensure:

- MSDSs are available to employees in their work areas during each work shift, and
- MSDS information is provided for each hazardous chemical.

C.9. Employee Responsibilities. Successful implementation of the Hazard Communication Program depends on active involvement of personnel at the WFO or WFO/RFC. Every NWS employee who purchases, handles, or uses hazardous chemical products is responsible:

- a. To know where to get information about the hazardous chemical labels used in the work area;

- b. To read and understand the information on hazardous chemical labels and MSDS;
- c. To keep the work area clean;
- d. To use protective clothing and equipment, as required;
- e. Not to smoke, eat, or drink around hazardous chemicals;
- f. To learn the emergency procedures for the work area;
- g. To follow the procedures for hazardous chemical disposal and spill cleanup;
- h. To practice safe work habits; and
- i. To attend required training.

C.10. On-site Contractors. When soliciting a contract, it is the Contracting Officer's Technical Representative (COTR) responsibility to inform the Contracting Officer of any possible hazards associated with work on a contract, so that notification and special conditions can be put into the solicitation prior to contract award. The site Safety or Environmental/Safety Focal Point shall advise the COTR of possible hazards that contractor employees encounter while working at an NWS facility. Contractors working at the WFO or WFO/RFC shall comply with the state of Missouri occupational safety and health regulations, Federal employees on the federal property are not.

The Contracting Officer shall obtain from a contractor a list of all chemicals the contractor intends to bring into or on to the work area (interior/exterior paint, sealants, tile or carpet adhesives, cleaning supplies, fertilizers, etc.). This includes construction as well as janitorial and landscaping contracts. A copy of the MSDS(s) shall be provided to the COTR and the Safety or Environmental/Safety Focal Point. MSDS(s) shall be posted in the work area, so that all employees affected by the contract work can have an access to them. If any engineering controls (ventilation, etc.) are required, the contractor shall describe the method(s) that shall be used to implement these controls.

Upon notification by the COTR, the Safety or Environmental/Safety Focal Point shall advise outside contractor employees of any hazards that they may encounter at NWS facilities. Contractor employees shall be informed about the location of this Hazard Communication Program and the availability of MSDS(s). The information provided by the Government shall be sufficient to enable the contractor to satisfy his own Hazard Communication Program responsibilities as promulgated by the

Missouri State OSHA-approved plan. In addition, the COTR shall ensure that contractor personnel have received Hazard Communication training in accordance with the Federal and state OSHA requirements (as applicable).

Section D - WORKSITE HAZARDOUS CHEMICAL LIST

Site/Location: Springfield, MO Region: Central

Address: 5805 W. Highway EE

Springfield-Branson Regional Airport

Springfield, MO 65802-5400

The following is a master chemical list of all known hazardous chemicals used at this facility. Further information on each noted chemical can be obtained by reviewing the worksite Material Safety Data Sheets (MSDS).

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Windshield lock de-icer	Tradeco	De-icer	On site office	1- 12 oz. spray can	1/17/00		WFO storeroom
Adhesive cyannoscrylate	Chemence Inc.	Cyanoconylate Adhesive	On site office	1- 1 oz. bottle	1/17/00	NSN8040-00-142-9193	WFO storeroom
Formula 409	The Clorox Co.	All purpose cleaner	On site office	2- 1 qt. bottles 1- 20 qt. refill bottle	1/17/00		WFO storeroom
X-14		Max Strength Mildew stain remover	On site office	1- 1 pt. spray bottle	1/17/00	2605718036	WFO storeroom
Polyurethane oil gloss enamel	Valspar	Enamel paint Bright red 23827	On site office	1- ½ pint can	1/17/00	PCI #762137	WFO storeroom
Liquid Seal	Macco Adhevisves	Clear Sealant	On site office	1- 5.5 oz. tube	1/17/00	CS 145	WFO storeroom
Carpenter's	Elmer's	Wood glue	On site	1- 7.6 oz. bottle	1/17/00	2600000701	WFO storeroom

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
wood glue			office				
Mercury Thermometers		Thermometer	On site office	8	1/17/00		WFO storeroom
Max/Min thermometers	Taylor	Thermometer	On site office	12	1/17/00	Model 5458	DAPN storage
Max thermometers	Kessler Instruments	Thermometer	On site office	10	1/17/00	Cat#WSNC102-2	Instrument shelter
Min thermometers	Kessler Instruments	Themometer	On site office	10	1/17/00	Cat#WSNC102-1	WFO storeroom
Tube Psychometer	Kessler Instruments	Themometer	On site office	5	1/17/00	Cat#WSNH000-3-1	WFO storeroom
Sling Psychometer	Kessler Instruments	Themometer	Instrument shelter	5	1/17/00	Cat#H055-1A	WFO storeroom
Sives Psychometer	Kessler Instruments	Themometer	On site office	2	1/17/00		WFO storeroom
BBGU Battery	Walters Industrial Electronics	Sealed rechargeable battery 6V	Rain gage	2	1/17/00	BP 10-6	WFO storeroom
Cyclan sealed rechargeable	Shelley-Regon	Sealed rechargeable	Rain gage	2	1/17/00	9118	WFO storeroom

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
battery		battery 6V					
Power Sonic Sealed Rechargeable battery	Power Sonic Corp.	Sealed rechargeable battery 6V	Rain gage	1	1/17/00	Model PS-6100	WFO storeroom
Cyalumme lightsticks	Omniglow Corp.	Snap lightsticks		5- 10 unit cases	1/17/00	Part # 9-27017	WFO storeroom
Cyalumme lightsticks	Omniglow Corp.	Snap lightsticks	UAIB	42- 10 unit cases	1/17/00	Part #9-27021	WFO storeroom
Gard SAE 10 API SA	Gard Corp.	Lubricating Oil	On site office	13 - 1 qt. bottles	1/17/00		WFO storeroom
Vaisala RS80 radiosonde	Vaisala	Radiosond battery	UAIB	400 units	1/17/00	RS80-57H	WFO storeroom
Propylene glycol		Antifreeze	Rain gage	8 quarts	1/17/00	NSA 6850-01-288-7922	WFO storeroom
ProMar 200	Sherwin Williams	Interior latex paint	On site office	1 gallon	1/17/00	4536-99993	WFO storeroom
Oil	Gard	Oil	On site office	5- 2oz. Bottles	1/17/00		WFO storeroom
Oil	Dow Corning	Oil	On site	3- 2oz. Bottles	1/17/00	6850-00904-	WFO storeroom

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
			office			3237	
Oil-silicone	Armistead	Oil	On site office	1- 4oz. Bottles	1/17/00	A-5601-4	WFO storeroom
Oil dash pot	Bel Fort	Oil	On site office	2- 3.5 oz. Bottles	1/17/00	No.6	WFO storeroom
Spray paint	Krylon	Paint	On site office	3- 11oz. Cans	1/17/00	RTA 9200	WFO storeroom
Ink/stamp pad	MTK Marking	Ink	On site office	2 oz.	1/17/00		WFO storeroom
Ink/stamp pad	American Writing	Ink	On site office	2 oz.	1/17/00	T510-00-161-4237	WFO storeroom
Ink/Instrument	Esterline Augus	Ink	On site office	16 oz.	1/17/00		WFO storeroom
Ink	Minneapolis Honeywell	Ink	On site office	1 oz.	1/17/00	74637-1	WFO storeroom
Ink	Bel Fort	Ink	On site office	½ oz.	1/17/00	#10 blk	WFO storeroom
Ink	Armistead Tech	Ink	On site office	1 oz.	1/17/00	5592-1	WFO storeroom

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Ink	NLSC	Ink	On site office	1 12 oz. bottle	1/17/00	751000-551-8394	WFO storeroom
Ink		Ink	On site office	1- 1 oz. bottle	1/17/00		WFO storeroom
Ink	Bristols	Ink	On site office	½ oz.	1/17/00	6883	WFO storeroom
Ink Pens	Graphic Controls	Ink	On site office	3 packs of 6	1/17/00	82-72-3181-06	WFO storeroom
Correction Fluid - Photo	Lee Products	Correction fluid	On site office	8- .68 fl. oz.	1/17/00	84417-18710	WFO storeroom
Ross Stik	American Glue Co.	Glue Stick	On site office	10- 1.41.oz. sticks	1/17/00	8040-01-360-8079	WFO storeroom
Real Kill wasp & hornet	Reclex	Bug spray	On site office	6- 1lb. 1oz. Cans	1/17/00	70116-10005	WFO storeroom
WD-40	WD-40	WD-40	On site office	1- 12.9 oz. can	1/17/00	10011	WFO storeroom
Home Best Insect Killer	Baytech	Bug Killer	On site office	1- 1 gallon jug	1/17/00	42384-36620	WFO storeroom
Print Cartridge	Hewlett Packard	Ink	Copy Room	6- 1.4 oz.	1/17/00	#HP576424	Copy Room

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Print Cartridge	Hewlett Packard	Ink	Copy Room	1- 1.4oz.	1/17/00	#HP51640M	Copy Room
Print Cartridge	Hewlett Packard	Ink	Ops	1- 1.4oz.	1/17/00	27X	Ops
Print Cartridge	Hewlett Packard	Ink	Computer room	1- 1.4oz.	1/17/00	92A	Computer Room
Print Cartridge	Hewlett Packard	Ink	Computer room	1- 1.4oz.	1/17/00	27X	Computer Room
Head Cleaner	Realistic	Head cleaner	On site office	1- 2oz. Bottle	1/17/00	cat# 44-10100	ET Shop
Professional tape head cleaner fluid	Realistic	Head cleaner	On site office	3- 2oz. Bottles	1/17/00	cat# 44-1113	ET Shop
Daal Magnetic eye cleaner		Head cleaner	On site office	2- 4oz. Bottles	1/17/00	NSN 7440-00336-3450	ET Shop
Regular glass Cleaner	Lighthouse for the blind	Glass cleaner	On site office	1- 8oz. Bottle	1/17/00	7930-00-664-6910	ET Shop
Adhesive cyanoacrylate	Chemence Inc.	Glue	On site office	4- 1 oz. Bottles	1/17/00	NSN 8040-00-142-9193	ET Shop

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Park Horse	The Piemler Co.	Video and Tape head cleaner	On site office	1- 8oz. Spray can	1/17/00		ET Shop
Heavy Duty Engine Degreaser	O'Reilly	Degreaser	On site office	1- 15oz. Spray can	1/17/00	part #72415	ET Shop
Staticide	ACL Inc.	Anti-static spray	On site office	1- 1qt. Bottle	1/17/00	#2010	ET Shop
H2SO4 Battery Cleaner	Noco	Battery cleaner	On site office	1- 14oz. Spray bottle	1/17/00	#E-404	ET Shop
Misty	Amrep Inc.	Contact/circuit board cleaner	On site office	6- 14oz. Spray cans	1/17/00	#362-16	ET Shop
Anderol Lubricant	Tenneco Chemicals	Synthetic time fuse oil	On site office	1- 3oz. Can	1/17/00	NA82WE-A-03521	ET Shop
Insecticide aerosol Synergized Pyrethring Type 1	Alosol Co.	Insect Killer	On site office	1- 12oz. Can	1/17/00	\$6840-823-7848	ET Shop
Pemert Heet	Dement & Dougherty	Fuel system antifreeze	On site office	1- 12oz. Spray can	1/17/00		ET Shop

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Freon TP-35	Texwipe Co.	Solvent Cleaner	On site office	1- 7oz. Bottle	1/17/00	TX116	ET Shop
Flux Remover and Cleaner	GC Electronics	Flux remover	On site office	1- 16oz. Can	1/17/00	#22-270	ET Shop
Johnson's De icer	Technical Chemicals	De-icer	On site office	1-12oz. Can	1/17/00	Part #3282	ET Shop
Blue Shower	Tech Spray Inc.	1,1,1 Trichloroethane	On site office	1 can	1/17/00	1677-125	ET Shop
Gray concrete crack sealer	The Quickrete Co.	Crack Sealer	On site office	1- 1qt. Bottle	1/17/00	#8640	ET Shop
Scotch Seal	3M Company	Industrial sealant	On site office	1- 24 oz. can	1/17/00	#612	ET Shop
Kester Soldering Flux	Litton Division	Soldering flux	On site office	1- 1 pt. bottle	1/17/00	Formula #1544	ET Shop
Multi-purpose Lithium	Cost to Cost	Grease	On site office	1- 14 ½ oz. can	1/17/00		ET Shop
All Temp grease	Texcco	Grease	On site office	1- 14 ½ Oz. Tube	1/17/00	MIL-G-10924A	ET Shop

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Molykote 33 grease	Dow Corning	Silicone grease	On site office	1- 5.3oz. Tube	1/17/00	#14710-99	ET Shop
Anemometer oil			On site office	1- ½ oz. tube	1/17/00		ET Shop
DE-OX-ID	GC Electronics	Contact cleaner	On site office	1- 2oz. Bottle	1/17/00	#210-2	ET Shop
Lubricating oil	Honeywell	Oil	On site office	1- 2oz. Bottle	1/17/00	B-15260	ET Shop
Polystyrene Q-dope	GC Electronics	Pipe dope	On site office	1- ½ oz tube	1/17/00	37-2	ET Shop
Plastic Rubber	Duro	Plastic Rubber	On site office	1- 1oz. Tube	1/17/00	PR-1	ET Shop
Dash Pot Liquid	BelFort Instrument	Oil	On site office	1- 1oz. Tube	1/17/00	#6	ET Shop
Epoxy Hardening Resin	GC Electronics	Super Glue	On site office	1- 3/4 oz. tube	1/17/00	40-100	ET Shop
Instant Bonding Adhesive	Archer	Glue	On site office	1- .11 oz. tube	1/17/00	64-2308 A	ET Shop

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
StatFree Spray	Perfect Dater	Static spray	On site office	3- 32oz. Bottles	1/17/00	PD6# 104578-1	Computer Room
Kleen Screen	Sunshine Chemicals	Cleaner	On site office	1- 18 oz. bottle	1/17/00		Computer Room
Soft Scrub w/ lemon cleanser	The Clorox Co.	Sink, Tub & Tile Cleaner	On site office	1- 31 oz. bottle	1/17/00	27543-IJJ	Break Room
Anti-bacterial disinfectant	Dow	Floor disinfectant	On site office	1- 4.3 oz. bottle	1/17/00	101406-0697CL	Break Room
Mr. Clean	Procter & Gamble	Floor cleaner	On site office	1- 28 oz. bottle	1/17/00	40080091	Break Room
Lysol Disinfectant spray	Lehn & Fink Products	Disinfectant spray	On site office	2- 18oz. Spray bottles	1/17/00		Break Room
General Purpose Detergent	Lighthouse for the Blind	General Purpose Cleaner	On site office	1- 16oz. Spray bottle	1/17/00	7930-00-926-5280	Break Room
Meter Mist Green Apple	Zep Manufacturing Company	Scent spray	On site office	1- 7oz. Spray can	1/17/00	3318	Break Room

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Lime-a-way	Benckiser Consumer Products	Bathroom Cleaner	On site office	1- 20 oz. bottle	1/17/00	739854155021	Break Room
Dove Dishwashing Liquid	Lever Bros. Co.	Dishwashing soap	On site office	1- 22oz. Bottle	1/17/00		Break Room
Ultra Palmolive	Colgate-Palmolive Company	Dishwashing soap	On site office	1- 46oz. Bottle	1/17/00		Break Room
Eye wash	Bausch & Lomb	Eyewash	On site office	1- 4oz. Bottle	1/17/00	620252	Break Room
Neosporin Plus	Warner Wellcome Consumer Health Products	Antibiotic ointment	On site office	1- 1oz. Tube	1/17/00		Break Room
Tums EX	Smith Kline Beecham	Calcium Tablets	On site office	1- 250 tablet bottle	1/17/00	0701XF	Break Room
Extra strength Tylenol Tablets	McNeil Consumer Health Products	Acetamenophen	On site office	1- 200 tablet bottle	1/17/00	7821211	Break Room
Sting Relief	Physicians &	Sting relief pads	On site	10 pads	1/17/00	90100	Break Room

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Pads	Nurses Mfg. Corp.		office				
The Itch Eraser	Tender Corp.	Sting relief pads	On site office	12 pads	1/17/00	053600R2	Break Room
Clorox Bleach	Clorox	Bleach	On site office	1 quart bottle	1/17/00		Janitor's Closet
Hand and Body Soap	Springfield Janitorial Supply	Soap	On site office	½ gallon container	1/17/00		Janitor's Closet
Bathroom Cleaner	Dow	Cleaner	On site office	25 oz. bottle	1/17/00		Janitor's Closet
Raid Bug Killer	Johnson & Johnson	Bug Killer	On site office	11 oz. bottle	1/17/00	46500-01672	Janitor's Closet
Sott Scrub	Clorox	Cleaner	On site office	26 oz. bottle	1/17/00	27454-IJJ	Janitor's Closet
Pennzoil	Pennzoil	Oil	On site office	1 quart	1/17/00	3653	Janitor's Closet
Klear Clean	Kleerite Mfg.	Cleaner	On site office	2- 6 oz. bottles	1/17/00		Janitor's Closet
409	Clorox	Cleaner	On site	2 quarts	1/17/00		Janitor's Closet

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
			office				
Glade Plug-In	Glade	Air freshener	On site office	7 boxes @ 7 oz. ea.	1/17/00		Restrooms
3M Cleaner	3M		On site office	1-.45 oz. spray can	1/17/00		Restrooms
Meter Mist	Zep Manufacturing Co.	Air freshener	On site office	1 7 oz. can	1/17/00		Restrooms
Bathroom Cleaner	Dow	Cleaner	On site office	1- 25 oz. cleaner	1/17/00		Restrooms
Incredible	Incredible	Stain remover	On site office	1- 16 oz.	1/17/00		Restrooms
Moles & Gophers Bait	WR Sweeney Inc.	Poison	On site office	2- 40 oz. containers	1/17/00		Restrooms
Hi Yield	Voluntary Purchasing	Poison	On site office	1- 16 oz. bottle	1/17/00		Restrooms
Tilex	Clorox Co.	Cleaner	On site office	1- 16 oz. bottle	1/17/00		Restrooms
Formula Pro	The Clorox Co.	Multi Purpose	On site	1- 22 oz. bottle	1/17/00	06366-JJ	Multi-Purpose

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
409		Cleaner	office				Room
Windex Multi Surface Cleaner	SC Johnson Wax Co.	Cleaner	On site office	1- 22 oz. bottle	1/17/00	407580	Multi-Purpose Room
Clean Sweep	Stempel Man. Co.	Dry Ink Board Cleaner	On site office	1- 8 oz. spray bottle	1/17/00	60-600	Multi-Purpose Room
Soft Scrub w/lemon	The Clorox Co.	Cleaner	On site office	1- 31.2 oz. bottle	1/17/00	62869.106JJ	Multi-Purpose Room
Spot Shot	Spot Shot Products	Carpet Stain Remover	On site office	1- 14 oz. spray can	1/17/00		Multi-Purpose Room
De-Solv-It	Orange-Sq 1 Household Products, Inc.	Cleaner	On site office	1- 12 oz. spray	1/17/00		Multi-Purpose Room
Glass Plus	Dow Chemicals	Glass/Surface cleaner	On site office	1- 32 oz. spray bottle	1/17/00	KG211216212	Multi-Purpose Room
Woolite Heavy Traffic Carpet Cleaner	Reckitt & Colman Inc.	Carpet Cleaner	On site office	1- 22 oz. spray bottle	1/17/00	955530	Multi-Purpose Room
Expo White	Anewell	Dry erase board	On site	1- 8 oz. spray	1/17/00	81803	Multi-Purpose

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Board Cleaner	Company	cleaner	office	bottle			Room
WD-40	WD-40 Company	Lubericant	RDA Shelter	1- 11oz. Spray can	1/17/00	1011	RDA Shelter
Wisk	Lever Co.	Detergent	RDA Shelter	1- 3.12 qt. bottle	1/17/00	62459-8351	RDA Shelter
Pro Formula 409	Clorox Company	Cleaner	RDA Shelter	1 32 oz. spray bottle	1/17/00	62459.1445	RDA Shelter
Parks	Parks Corp.	Cleaner	RDA Shelter	1- 32 oz. spray bottle	1/17/00	2125	RDA Shelter
Baby Powder	H & H Labs	Talc powder	RDA Shelter	1- 14 oz. bottle	1/17/00	3563-14007	RDA Shelter
Zinc-Rich	Rust-oleum	Paint	RDA Shelter	2- 20 oz. spray cans	1/17/00	U2185	RDA Shelter
American Accent	Rust-oleum	Paint	RDA Shelter	3- 20 oz. spray cans	1/17/00	7942	RDA Shelter
Silicon Sealant	Dow Corning	Silicone	RDA Shelter	2- tubes	1/17/00	732	RDA Shelter
Tecstar Fibrebond	PPG	Spray paint	RDA Shelter	1- 12 oz. spray can	1/17/00		RDA Shelter

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Krylon	Sherwin Williams Co.	Paint	RDA Shelter	1- 12 oz. spray can	1/17/00	1502	RDA Shelter
Koeler Cream	Kohler Co.	Paint	RDA Shelter	1- 12 oz. spray can	1/17/00	15723	RDA Shelter
Paint		Interior tan paint	RDA Shelter	1- 1qt. Can	1/17/00	12595	RDA Shelter
Paint		Interior white paint	RDA Shelter	1- 1qt. Can	1/17/00	12845	RDA Shelter
Paint		Roofstop coat	RDA Shelter	1- 1qt. Can	1/17/00	13682	RDA Shelter
Paint		Aggrebrite Rock coating	RDA Shelter	1- 1 pt. can	1/17/00	11369	RDA Shelter
Paint	FibreBond Inc.	Floor Paint Part A	RDA Shelter	1- 1pt. Can	1/17/00		RDA Shelter
Adhesive	FibreBond Inc.	Expxy glue part A	RDA Shelter	1- 1pt. Can	1/17/00	11371	RDA Shelter
Paint	FibreBond Inc.	Floor paint Part B	RDA Shelter	1- 1pt. Can	1/17/00		RDA Shelter
Adhesive	FibreBond Inc.	Expoxy glue part	RDA	1- 1pt. Can	1/17/00		RDA Shelter

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
		B	Shelter				
Paint	FibreBond Inc.	Thorulastic mesatan	RDA Shelter	1- 1qt. Can	1/17/00	11243	RDA Shelter
Paint	FibreBond Inc.	Thorseal texturizer	RDA Shelter	1- 1pt. Can	1/17/00		RDA Shelter
Lightweight Spackling Paste	Bondex International		RDA Shelter		1/17/00		RDA Shelter
Isopropyl Alcohol	Perrigo	Alcohol	RDA Shelter	1-1pt. Bottle	1/17/00	0113-3804-43	RDA Shelter
Shell Diala Oil AX	Ashland Chemical	Oil	RDA Shelter	3 - 5 gallon containers	1/17/00	7125999	RDA Shelter
Premium Blue	Valvoline	SAE 15-40W	RDA Shelter	1- 1gallon container	1/17/00	70509	RDA Shelter
Zerex	Valvoline	Antifreeze	RDA Shelter	1- 1 gallon container	1/17/00	2888250001	RDA Shelter
#2 Diesel Fuel	Maynard Oil Co.	Diesel Fuel	RDA Shelter	500 gallons	1/17/00	NSN 9140-00-286-5294	RDA Shelter
#2 Diesel Fuel	Maynard Oil Co.	Diesel Fuel	Generator	1000 gallons	1/17/00	NSN 9140-00-	Generator

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
			Building			286-5294	building
Exsorbet	Exsorbet Industries	Oil Clean	Generator Building	2 bags	1/17/00		Generator building
Motor Oil	Valvoline	Oil	Generator Building	4- 1 gallon containers	1/17/00	70509	Generator building
Tex Wipes	Tex Wipes Co.	Wipe	Generator Building	37 boxes	1/17/00	Tx-801	Generator building
Acrylic Latex Gloss Enamel	Valspar	Paint	Generator Building	1 quart	1/17/00		Generator Bdlg. Storeroom
Gunk	Radiator Specialty Co.	Gunk	Generator Building	1- 13 ounce can	1/17/00	78698-13095	Generator Bdlg. Storeroom
Behr	Behr Process	Oil stain remover	Generator Building	1- 1 quart container	1/17/00		Generator Bdlg. Storeroom
Lyt-All	Pratt & Lambert	Paint	Generator Building	1 30 oz. can	1/17/00	675	Generator Bdlg. Storeroom
Lig- Nails	MACCOA Adhesives	Glue	Generator Building	1 tube	1/17/00	0600413	Generator Bdlg. Storeroom
Silicone Rubber	General Electric	Caulk	Generator Building	1 tube	1/17/00	GE-012	Generator Bdlg. Storeroom

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Ice Melt	Scottwood Inc.	Sodium Chloride	Generator Building	120 lbs.	1/17/00		Generator Bldg. Storeroom
House Paint	Colgny	Paint	Generator Building	1 gallon	1/17/00	8500	Generator Bldg. Storeroom
Lacquer thinner	Klean Strip	Mineral Spirits	Generator Building	1- 32 oz. container	1/17/00	ML-170	Generator Bldg. Storeroom
Isopropyl Alcohol	Meda List	Alcohol	Generator Building	2 - 1 gallon containers	1/17/00	NOC-37937-005-40	Generator Bldg. Storeroom
Battery Protector	Sherwin Williams	Cleaner	Generator Building	1- 4 oz. can	1/17/00	1307	Generator Bldg. Storeroom
Enamel	Krylon Sherwin Williams	Spray paint	Generator Building	2- 11 oz. cans	1/17/00		Generator Bldg. Storeroom
Truck and Van Paint	Cutter Products	Spray paint	Generator Building	1- 11 oz. spray can	1/17/00		Generator Bldg. Storeroom
Spray Paint	Wal Mart	Spray paint	Generator Building	1- 12 oz. can	1/17/00		Generator Bldg. Storeroom
Spray Laquer	Pacific Aerosol	Spray paint	Generator Building	1- 16 oz. can	1/17/00		Generator Bldg. Storeroom
Spray Paint	Dupli- Color	Paint	Generator	1- 12 oz. can	1/17/00	OFE-16	Generator Bldg.

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
			Building				Storeroom
Spray Paint	Krylon	Paint	Generator Building	2- 12 oz. cans	1/17/00	8102	Generator Bdlg. Storeroom
Battery Cleaner	NOCO	Cleaner	Generator Building	1- 14 oz. can	1/17/00	E-404	Generator Bdlg. Storeroom
Spray Paint	Dupli-Color	Paint	Generator Building	1- 10 oz. can	1/17/00	LF129	Generator Bdlg. Storeroom
Acetone	Klean-strip	Acetone	Generator Building	1 quart	1/17/00	AC-18	Generator Bdlg. Storeroom
Ultra Hide	Glidden	Latex Paint	Generator Building	1 gallon can	1/17/00	UH5800	Generator Bdlg. Storeroom
Ultra Hide	Glidden	Latex Paint	Generator Building	6- 1 gallon cans	1/17/00	UX6800	Generator Bdlg. Storeroom
Ultra Hide	Glidden	Latex Paint	Generator Building	1 gallon can	1/17/00	UH6810	Generator Bdlg. Storeroom
Preen-Green	Greenview	Weed killer	Generator Building	22 lbs.	1/17/00	30465	Generator Bdlg. Storeroom
Paint	Benjamin Moore	Paint	Generator Building	1 gallon can	1/17/00	5-235-5A	Generator Bdlg. Storeroom

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Paint	Glidden	Latex Paint	Generator Building	1 gallon can	1/17/00	6780	Generator Bldg. Storeroom
Lubricating Oil	Caid Corp	Oil	Generator Building	1 quart container	1/17/00		Generator Bldg. Storeroom
Lubriplate	Fiske Bros.	Grease	Generator Building	2- 14 oz containers	1/17/00		Generator Bldg. Storeroom
Anderol	Tenneco	Synthetic lubricant	Generator Building	1 pound	1/17/00		Generator Bldg. Storeroom
33 Grease	Dow Corning	Grease	Generator Building	1 5.3 oz. tube	1/17/00		Generator Bldg. Storeroom
Form-a-gasket	Permatex	Gasket material	Generator Building	1 tube	1/17/00	#2	Generator Bldg. Storeroom
Kleen Glean	Kleerite	Cleaner	Generator Building	1 - 6oz. Can	1/17/00	7510-00-616-9580	Generator Bldg. Storeroom
Torn-Lable	Lighthouse	Alcohol	Generator Building	1 8 Oz. Can	1/17/00		Generator Bldg. Storeroom
2 cycle Engine Oil	Sears	Oil	Generator Building	6 - 3.2 oz. cans	1/17/00	36552	Generator Bldg. Storeroom
Windshield	Homestar	Cleaner	Generator	2 - 1 gallon	1/17/00		Generator Bldg.

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Washer			Building	containers			Storeroom
Spectracide	Spectracide	Weed Killer	Generator Building	1 6.4 oz. bottle	1/17/00	71121-56100	Generator Bldg. Storeroom
Muriatic Acid	Sunnyside	Hydronic Acid	Generator Building	1- 1 gallon container	1/17/00	7652-00056	Generator Bldg. Storeroom
Miracid	Miracle- Gro	Fertilizer	Generator Building	3 lbs.	1/17/00	FKKB0720-1014	Generator Bldg. Storeroom
Miracle Gro	Miracle-Gro	Fertilizer	Generator Building	10 lbs.	1/17/00	15-30-15	Generator Bldg. Storeroom
Road Runner Ice Melt			UAIB	1 50 lb. Bag	1/17/00		UAIB
Hydrogen	Air Products Chemicals	Hydrogen	UAIB	60 2000 psi containers	1/17/00	NSN 6830-00-NO7-5377	UAIB
Helium			UAIB		1/17/00		UAIB
WD-40	WD-40 Co.	Lubricant	UAIB	1- 90z. Spray can	1/17/00		UAIB
Isopropyl Alcohol	Cumberland	Isopropyl Alcohol	County Warning Area	1- 16 oz. bottle	1/17/00	816-25	ET Van
Laquer			County				

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Thinner	W. M. Barrt Co.	Mineral Spirits	Warning Area	1- 32 oz. can	1/17/00	ML-170	ET Van
Super Color 134 Plus	MC Chemicals	1,1,1,2 tetraflouroethane	County Warning Area	3- 14 oz. spray cans	1/17/00	40-3A4007	ET Van
Hornet & Wasp Killer	Ortho	Bug killer	County Warning Area	1- 15 oz. spray	1/17/00	816-25	ET Van
WD-40	WD-40 Company	Lubricant	County Warning Area	1- 14 oz. spray can	1/17/00	10011	ET Van
Insect Repellant Spray	Cutter	Bug Spary	County Warning Area	1- 14 oz. spray can	1/17/00	0161-0536-54	ET Van
Battery Protector	Krylon	Paint	County Warning Area	1 - 11 oz. spray can	1/17/00	1307	ET Van
Round Up Weed and Grass Killer	Solaris Group	Weed Killer	County Warning Area	1- 32 oz. spray bottle	1/17/00	70183-50010	ET Van
LCR	Panasonic	Battery	KSGF	5	1/17/00	NSN 6140-01-	KSGF ASOS

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
12V17CP			ASOS			417-9154	
LCR 12V17CP	Panasonic	Battery	ASOS	1	1/17/00	NSN 6140-01-417-9154	ASOS
PS-1270	Power Sonic	Battery	LARC	1	1/17/00	NSN-6140-01-108-7120	ET Storage room
LCR 12V17CP	Panasonic	Battery	KSGF ASOS	5	1/17/00	NSN 6140-01-417-9154	KSGF ASOS (field)
LRC 12v17CP	Panasonic	Battery	KJLN ASOS	4	1/17/00	NSN 6140-01-417-9154	KJLN ASOS (field)
LRC 12v17CP	Panasonic	Battery	KJLN ASOS	4	1/17/00	NSN 6140-01-417-9154	KJLN ASOS (field)
LRC 12v17CP	Panasonic	Battery	KVIH ASOS	4	1/17/00	NSN 6140-01-417-9154	KVIH ASOS (field)
LRC 12v17CP	Panasonic	Battery	KVIH ASOS	4	1/17/00	NSN 6140-01-417-9154	KVIH ASOS (field)
Motor Oil	Havoline	Oil10W30	Avilla, MO	3 quarts	1/17/00	NSN 9150-00-NO2-1986	WXJ-61
Propane	Maynard Fuel Oil Co.	Propane	Avilla, MO	250 Gallon tank	1/17/00	NSN 6830-00-NO3-2803	WXJ-61

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
Autolite	AC Delco	12V lead acid battery	Avilla, MO	1	1/17/00	NSN 6140-01-355-2013	WXJ-61
PS-12260	Power Sonic	12V - 7AH		1each	1/17/00	NSN 6140-01-346-8316	Jerome & Fulton
PS-12260	Power Sonic	12V - 7AH		1each	1/17/00	NSN 6140-01-108-2159	Other 7 LARC
DESC		Lubricating Oil	RAMDO ME	10 gallons	1/17/00	NSN 9150-01-000-0001-X	RANDOME
Molybdenum Disulfide		Grease	RAMDO ME	3 - 14 oz. canisters	1/17/00	NSN 9150-00-935-4018	RANDOME
Shell Diala Oil Ax	Ashland Chemical Co	Lubricating Oil	Radome	5 Gal Container	1/17/00	7125999	Radome
Exorbet	Exorbet Industries	Oil Absorbent	Radome	Trial Size Bag	1/17/00	nsn:mn59-70-590-6004	Radome
Lubrimatic	Lubrimatic Start Corp	Multi-purpose Lithium Grease	Radome	3 oz. tube	1/17/00		Radome
Sta-Lubs	CRC	Lithium General Purpose Grease	Radome	14 oz. tube	1/17/00		Radome
GMD	Shell Oil	Grease	Radome	2-14 oz tubes	1/17/00		Radome

HAZARDOUS CHEMICAL LIST							
Product Name on Label	Manufacturer Listed on Label	Generic Name	Operation / Work Area Used	Quantity on Hand (oz., gal, ltr, lbs., tons)	Date entered into system	ASN, NSN, or Part #	Location Stored
		Molybdenum Disulfide					
Lube Oil	Cage: NLB48	Lube oil	Radome	5 gal container	1/17/00		Radome
Hornet & Wasp Killer	Ortho	Bug srpay	Radome	1 - 15 oz. spray can`	1/17/00		Radome

Section G - WORK SITE TRAINING RECORDS

SITE NAME: Springfield, MO Weather Forecast Office

Title	Name	Training Date
Administrative Assistant	Snell, Dee	April 24, 1998
Electronic Technician	Tomash, Mark	
Forecasters	Albert, Drew	July 29, 1999
Forecasters	Shumway, Steve	March 15, 1998
Forecasters	Steinmetz, Dean	March 15, 1998
Forecasters	Taggart, Jim	February 28, 1998
Forecasters	Terry, Megan	August 26, 1998
Management	Gaede, Dave	March 3, 1998
Management	Lyon, Charlie	March 25, 1998
Management	Murphy, Paul	March 15, 1998
Management	Runnels, Steve	April 19, 1998
Metorological Technicians and	Bookbinder, Evan	June 30, 1999
Metorological Technicians and	Cissell, David	June 15, 1999
Metorological Technicians and	Dooley, Larry	April 15, 1999
Metorological Technicians and	Hatch, Fred	August 4, 1999
Metorological Technicians and	Johnson, Gary	April 20, 1998
Metorologist in Charge	Davis, William	April 15, 1999
Senior Forecasters	Foster, Andy	May 15, 1999
Senior Forecasters	Hudson, Mike	
Senior Forecasters	Lindenberg, Steve	March 15, 1998
Senior Forecasters	Rickard, Chuck	September 30, 1998
Senior Forecasters	Sutton, Mike	February 28, 1998