

### Local Climatological Data Hourly Observations June 1986

Current Location: Elev: 38 ft. Lat: 30.2050° N Lon: -91.9875° W

Generated on 03/24/2023

Station: LAFAYETTE REGIONAL AIRPORT, LA US WBAN: 72240513976 (KLFT)

| Date | Time (LST) | Station Type | Sky Conditions | Visi-<br>bility | Weather Type (see documentation) | Dry Bulb Temp |      | Wet Bulb Temp |     | Dew Point Temp |      | Rel Hum % | Wind Speed (MPH) | Wind Dir (Deg) | Wind Gusts (MPH) | Station Press (inHg) | Press Tend | Net 3-Hr Change (inHg) | Sea Level Press (inHg) | Report Type | Precip Total (in) | Alti-<br>meter Setting (inHg) |
|------|------------|--------------|----------------|-----------------|----------------------------------|---------------|------|---------------|-----|----------------|------|-----------|------------------|----------------|------------------|----------------------|------------|------------------------|------------------------|-------------|-------------------|-------------------------------|
|      |            |              |                |                 | AU   AW   MW                     | (F)           | (C)  | (F)           | (C) | (F)            | (C)  |           |                  |                |                  |                      |            |                        |                        |             |                   |                               |
| 1    | 2          | 3            | 4              | 5               | 6                                | 7             | 8    | 9             | 10  | 11             | 12   | 13        | 14               | 15             | 16               | 17                   | 18         | 19                     | 20                     | 21          | 22                | 23                            |
| 25   | 0100       | 4            |                | 6.96            |                                  | 76            | 24.4 |               |     | 71             | 21.7 | 85        | 5                | 080            |                  |                      |            |                        | 29.98                  | SAO         |                   | 29.99                         |
| 25   | 0200       | 4            |                | 6.96            |                                  | 75            | 23.9 |               |     | 72             | 22.2 | 90        | 6                | 060            |                  |                      |            |                        | 29.98                  | SAO         |                   | 29.97                         |
| 25   | 0300       | 4            |                |                 |                                  | 75            | 23.9 |               |     | 72             | 22.2 | 90        | 5                | 060            |                  |                      | 6          | +0.02                  | 29.97                  | SAO         |                   | 29.97                         |
| 25   | 0400       | 4            |                | 6.96            |                                  | 75            | 23.9 |               |     | 72             | 22.2 | 90        | 7                | 040            |                  |                      |            |                        | 29.98                  | SAO         |                   | 29.98                         |
| 25   | 0500       | 4            |                | 5.97            | HZ FG                            | 75            | 23.9 |               |     | 72             | 22.2 | 90        | 7                | 060            |                  |                      |            |                        | 30.00                  | SAO         |                   | 30.00                         |
| 25   | 0600       | 4            |                | 5.97            | HZ FG                            | 76            | 24.4 |               |     | 73             | 22.8 | 91        | 8                | 050            |                  |                      | 1          | -0.04                  | 30.01                  | SAO         |                   | 30.00                         |
| 25   | 0700       | 4            |                | 5.97            | HZ FG                            | 80            | 26.7 |               |     | 75             | 23.9 | 85        | 8                | 080            |                  |                      |            |                        | 30.02                  | SAO         |                   | 30.02                         |
| 25   | 0800       | 4            |                | 5.97            | HZ                               | 83            | 28.3 |               |     | 74             | 23.3 | 74        | 13               | 080            |                  |                      |            |                        | 30.02                  | SAO         |                   | 30.02                         |
| 25   | 0900       | 4            |                | 6.96            |                                  | 86            | 30.0 |               |     | 73             | 22.8 | 65        | 14               | 100            |                  |                      | 1          | -0.01                  | 30.02                  | SAO         |                   | 30.02                         |
| 25   | 1000       | 4            |                | 6.96            |                                  | 87            | 30.6 |               |     | 73             | 22.8 | 63        | 11               | 080            |                  |                      |            |                        | 30.03                  | SAO         |                   | 30.03                         |
| 25   | 1100       | 4            |                | 6.96            |                                  | 87            | 30.6 |               |     | 72             | 22.2 | 61        | 14               | 110            |                  |                      |            |                        | 30.03                  | SAO         |                   | 30.03                         |
| 25   | 1200       | 4            |                | 6.96            |                                  | 82            | 27.8 |               |     | 74             | 23.3 | 77        | 11               | 110            |                  |                      | 5          | 0.00                   | 30.03                  | SAO         |                   | 30.04                         |
| 25   | 1300       | 4            |                | 6.96            |                                  | 82            | 27.8 |               |     | 72             | 22.2 | 72        | 17               | 180            |                  |                      |            |                        | 30.04                  | SAO         |                   | 30.04                         |
| 25   | 1400       | 4            |                | 6.96            |                                  | 86            | 30.0 |               |     | 75             | 23.9 | 70        | 6                | 160            |                  |                      |            |                        | 30.01                  | SAO         |                   | 30.01                         |
| 25   | 1500       | 4            |                | 6.96            |                                  | 83            | 28.3 |               |     | 73             | 22.8 | 72        | 8                | 130            |                  |                      | 8          | +0.04                  | 29.99                  | SAO         |                   | 29.99                         |
| 25   | 1600       | 4            |                | 6.96            |                                  | 86            | 30.0 |               |     | 73             | 22.8 | 65        | 11               | 090            |                  |                      |            |                        | 29.98                  | SAO         |                   | 29.98                         |
| 25   | 1700       | 4            |                | 6.96            |                                  | 86            | 30.0 |               |     | 73             | 22.8 | 65        | 9                | 110            |                  |                      |            |                        | 29.98                  | SAO         |                   | 29.98                         |
| 25   | 1800       | 4            |                | 6.96            |                                  | 84            | 28.9 |               |     | 74             | 23.3 | 72        | 10               | 120            |                  |                      | 5          | +0.01                  | 29.98                  | SAO         |                   | 29.98                         |
| 25   | 2000       | 4            |                | 6.96            |                                  | 79            | 26.1 |               |     | 71             | 21.7 | 77        | 11               | 090            |                  |                      |            |                        | 30.00                  | SAO         |                   | 30.00                         |
| 25   | 2100       | 4            |                | 6.96            |                                  | 78            | 25.6 |               |     | 72             | 22.2 | 82        | 11               | 100            |                  |                      | 1          | -0.02                  | 30.00                  | SAO         |                   | 30.00                         |
| 25   | 2200       | 4            |                | 6.96            |                                  | 77            | 25.0 |               |     | 73             | 22.8 | 88        | 9                | 100            |                  |                      |            |                        | 30.01                  | SAO         |                   | 30.01                         |
| 25   | 2300       | 4            |                | 6.96            |                                  | 77            | 25.0 |               |     | 72             | 22.2 | 85        | 10               | 100            |                  |                      |            |                        | 30.01                  | SAO         |                   | 30.01                         |

U.S. Department of Commerce  
National Oceanic & Atmospheric Administration  
National Environmental Satellite, Data, and Information Service

**Local Climatological Data**  
**Hourly Remarks**  
**June 1986**  
Generated on 03/24/2023

National Centers for Environmental Information  
151 Patton Avenue  
Asheville, North Carolina 28801

Current Location: Elev: 38 ft. Lat: 30.2050° N Lon: -91.9875° W

Station: **LAFAYETTE REGIONAL AIRPORT, LA US WBAN: 72240513976 (KLFT)**

| Date | Time (LST) | Remarks                             |
|------|------------|-------------------------------------|
| 25   | 0300       | AWY004608?                          |
| 25   | 0600       | AWY025CB W/ 112 ? 75?               |
| 25   | 0700       | AWY005CB W?                         |
| 25   | 0800       | AWY005CB W?                         |
| 25   | 0900       | AWY004105?                          |
| 25   | 1200       | AWY041CB S-NW ? RB05E27/ 10 501 75? |
| 25   | 1300       | AWY026CB ? OVHD-S-NW?               |
| 25   | 1400       | AWY009CB NE-SE?                     |
| 25   | 1500       | AWY004815?                          |
| 25   | 1700       | AWY006CB SE?                        |
| 25   | 1800       | AWY007503 88?                       |
| 25   | 2100       | AWY004107?                          |

## Local Climatological Data Hourly Precipitation June 1986

Current Location: Elev: 38 ft. Lat: 30.2050° N Lon: -91.9875° W

Generated on 03/24/2023

Station: **LAFAYETTE REGIONAL AIRPORT, LA US WBAN: 72240513976 (KLFT)**

| Date                                 | For Hour (LST) Ending at |      |      |      |      |      |      |      |      |       |       |      |      |      |      |      |      |      |      |      |      |       |       |     | Date |
|--------------------------------------|--------------------------|------|------|------|------|------|------|------|------|-------|-------|------|------|------|------|------|------|------|------|------|------|-------|-------|-----|------|
|                                      | 1 AM                     | 2 AM | 3 AM | 4 AM | 5 AM | 6 AM | 7 AM | 8 AM | 9 AM | 10 AM | 11 AM | NOON | 1 PM | 2 PM | 3 PM | 4 PM | 5 PM | 6 PM | 7 PM | 8 PM | 9 PM | 10 PM | 11 PM | MID |      |
| Maximum Short Duration Precipitation |                          |      |      |      |      |      |      |      |      |       |       |      |      |      |      |      |      |      |      |      |      |       |       |     |      |
| Time Period (Minutes)                | 5                        | 10   | 15   | 20   | 30   | 45   | 60   | 80   | 100  | 120   | 150   | 180  |      |      |      |      |      |      |      |      |      |       |       |     |      |
| Precipitation (inches)               |                          |      |      |      |      |      |      |      |      |       |       |      |      |      |      |      |      |      |      |      |      |       |       |     |      |
| Ending Date Time<br>(yyyymmdd hh:mi) |                          |      |      |      |      |      |      |      |      |       |       |      |      |      |      |      |      |      |      |      |      |       |       |     |      |

Hourly, daily, and monthly totals on the Daily Summary page and the Hourly Precipitation Table are shown as reported by the instrumentation at the site. However, NWS does not edit hourly values for its ASOS sites, but may edit the daily and monthly totals for selected sites which will be reflected on the Daily Summary page.

T = Trace  
 s = Suspect  
 \* = Erroneous  
 blank = No precipitation observed  
 M = Missing