

Naming Convention for SHEF Data Value Tables

For the RFC Archive Database a new naming convention for the majority of the data value tables was implemented. This naming convention is based on the SHEF “pedtsep” acronym where the “t”, type code) and optionally the “d” duration code indicate the type of data stored in the table.² There are three exceptions to this naming convention, these are the tables commentvalue, pairedvalues and unkstnvalue which are a carryover from the IHFS database.

Table Name	Description
pedrsep	non-specific single value, Reading (observed) (duration codes (K, L, D & P)
pecrsep	15-min to 6-hour time step data, Reading (observed)
pedfsep	non-specific single value, Forecast
pehfsep	1-hour time step data, Forecast
peqfsep	6-hour time step data, Forecast
pedcsep	any duration data, Contingency
pemrsep	monthly values, Reading (observed) data
pedpsep	daily values, Processed Observed data
pehpsep	1-hour time step data, Processed Observed data
peqpsep	6-hour time step data, Processed Observed data
pempsep	monthly values, Processed Observed data
peoosep	catch-all table for shef_decoder_raw, “o” is for other, observed data only
commentvalue	Reading (observed) or Forecast data that is coded with a Retained Comment
pairedvalues	vector data,observed or forecast based on SHEF pe types as described in Table 22 of the SHEF ver2.0 manual
unkstnvalue	Reading or Forecast data for a site that is not defined in the location table

² This concept was developed by Arthur Henkel, CNRFC located in Sacramento, CA.